

EXTRACTOR PLUNGER ASSEMBLY FOR GLOCK® GEN 3 - SHADOW SYSTEMS EXTRACTOR PLUNGER ASSEMBLY FOR GLOCK GEN 3

[Handgun Parts](#) > [Action Parts](#) > [Extractor Parts](#) > [Extractor Plungers](#)

The Shadow Gunworks Extractor Plunger Assembly is just what you need to replace the worn out parts of your Gen 3 Glock. Kit includes: 4140 Nitride Coated Extractor Depressor Plunger 302 Stainless Steel Extractor Depressor Spring Nylon 6 Spring Loaded Bearing Fits Glock 17, 19, 26, 34



Attributes

- Name: [SHADOW SYSTEMS EXTRACTOR PLUNGER ASSEMBLY FOR GLOCK GEN 3](#)
- Manufacturer: [SHADOW SYSTEMS](#)
- Product no.: 100024237
- Mfr. No.: SGK-1008
- Model: 19,26,34,17
- Weapon type: Glock
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 25mm
- Shipping length: 25mm
- UPC: 853687007714

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Extractor Plunger Assembly for Glock® Gen 3](#)
- [About Us](#)

Safety Instruction Guide for Extractor Plunger Assembly for Glock® Gen 3

Introduction

Thank you for choosing the Shadow Gunworks Extractor Plunger Assembly for your Glock® Gen 3. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the product is compatible with your specific Glock® model (17, 19, 26, or 34).
- Always handle firearms and firearm components with care and responsibility.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the product for wear and damage before use.
- Store the product in a secure location when not in use.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about product recalls through the EU Safety Gate platform.

Specific Safety Precautions for Use

- Wear appropriate safety gear, including safety glasses and gloves, when handling or installing the extractor plunger assembly.
- Ensure the firearm is unloaded before beginning any installation or maintenance work.
- Avoid using excessive force during installation to prevent damage to the firearm or the product.
- Do not modify the product in any way that could affect its performance or safety.
- Ensure that all components are correctly installed and functioning before using the firearm.

Instructions for Installation and Usage

Installation Steps

1. Preparation:

- Ensure your firearm is completely unloaded.
- Gather necessary tools for installation, including a punch tool and a small hammer.

2. Remove the Old Extractor Plunger Assembly:

- Disassemble your Glock® according to the manufacturer's instructions.
- Locate the old extractor plunger assembly.
- Use the punch tool to carefully remove the old extractor depressor plunger and spring.

3. Install the New Extractor Plunger Assembly:

- Take the new 4140 Nitride Coated Extractor Depressor Plunger and the 302 Stainless Steel Extractor Depressor Spring from the kit.
- Insert the new extractor depressor plunger into the designated space.
- Follow with the extractor depressor spring, ensuring it is seated properly.

4. Reassemble the Firearm:

- Carefully reassemble your Glock® according to the manufacturer's instructions.
- Perform a function check to ensure everything is working correctly.

5. Final Inspection:

- Inspect the installation to ensure that all components are secure and functioning as intended.

Usage Guidelines

- After installation, test the firearm in a safe and controlled environment.
- Regularly check the extractor plunger assembly for signs of wear or damage.
- Follow all local laws and regulations regarding the use of firearms.

Disposal Instructions

- Dispose of any old or unused parts in accordance with local regulations.
- If the product is damaged or no longer usable, contact your local waste management service for proper disposal methods.

Contact Information for Further Support

For any inquiries regarding the safety or performance of the Shadow Gunworks Extractor Plunger Assembly, please reach out to the designated EU contact point provided with your product packaging or documentation.

This safety instruction guide is designed to ensure the safe use of your Shadow Gunworks Extractor Plunger Assembly for Glock® Gen 3. Adhering to these guidelines will help you maintain safety and compliance with EU regulations. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk