

## ELLIASON SIGHT ELEVATION SCREW, 6-64 THREAD

The replacement Kensight Elliason? Elevation Screw can be used to replace the screw on both the original Elliason? and those manufactured by Kensight. Specifications: 6-64 Sight Body Dimensions: .330" long; Head: .115" x .210" dia; Threads: .215" x .131" dia.



### Attributes

- Name: [ELLIASON SIGHT ELEVATION SCREW, 6-64 THREAD](#)
- Manufacturer: [KENSIGHT MFG.](#)
- Product no.: 100034481
- Mfr. No.: 840110
- Delivery weight: 0.009kg
- Shipping height: 3mm
- Shipping width: 89mm
- Shipping length: 152mm
- UPC: 755377841106

# Table of Contents

- Startpage
- ELLIASON SIGHT ELEVATION SCREW Safety Instructions
- About Us

# ELLIASON SIGHT ELEVATION SCREW Safety Instructions

## Introduction

Thank you for choosing the ELLIASON SIGHT ELEVATION SCREW. This guide provides important safety information, installation instructions, and disposal guidelines to ensure safe use of the product. Please read this guide carefully before using the product.

## General Safety Guidelines

- Ensure that the ELLIASON SIGHT ELEVATION SCREW is used only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the product for any signs of wear or damage before each use.
- If you notice any defects, do not use the product and contact the manufacturer for assistance.
- Follow all instructions carefully to avoid accidents and injuries.

## Specific Safety Precautions for Use

- Only use the ELLIASON SIGHT ELEVATION SCREW with compatible sight bodies as specified.
- Do not modify or alter the screw in any way.
- Ensure that the screw is securely tightened to prevent it from loosening during use.
- Avoid using excessive force when installing or adjusting the screw to prevent damage.
- If you are unsure about the installation or use, seek assistance from a qualified professional.

## Instructions for Installation and Usage

### 1. Preparation

- Gather all necessary tools for installation, including a screwdriver compatible with the screw head.
- Ensure that the work area is clean and welllit.

### 2. Installation Steps

- Remove the existing elevation screw from the sight body by turning it counterclockwise.
- Align the new ELLIASON SIGHT ELEVATION SCREW with the threaded hole in the sight body.
- Insert the screw and turn it clockwise to tighten. Ensure it is snug but do not overtighten.
- Verify that the screw is securely in place and that there is no wobbling.

### 3. Usage Tips

- Adjust the elevation of your sight as needed using the installed screw.
- Regularly check the screw for tightness during use, especially after heavy use or adjustments.

## Disposal Instructions

- Dispose of the ELLIASON SIGHT ELEVATION SCREW in accordance with local regulations.
- Do not dispose of the product in general household waste.
- If the product is damaged or no longer needed, consider recycling it if possible.

## **Contact Information for Further Support**

For any safety inquiries, product issues, or to report unsafe conditions, please reach out to the manufacturer or your local safety authority. Always ensure that you have the most current information regarding product safety and recalls.

Thank you for your attention to these safety guidelines. Your safety is our priority.

# About Us

## Brownells Italia

**Brownells Italia - The shop of the largest dealer of components and accessories for target shooting guns, defense and hunting**

**Sede Legale enbsp; Operativanbsp;**

Brownells Italia Srlnbsp;

Via Dante Alighieri 163

25068nbsp; Sarezzo Bs

P.Iva e C.F. IT02801420981

[www.brownells.it](http://www.brownells.it)