

# XRT X-RINGS PICATINNY SCOPE RINGS - TPS PRODUCTS XRT ALUMINUM RINGS 30MM S-LOW

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

XRT Series X-Rings, bringing a whole new level of beauty and precision into an extremely rugged Picatinny platform scope mount. The X-Rings have been built from the bottom up to provide the extreme precision and accuracy that TPS rings have been known for over the last two decades. The ring bases begin from a solid billet of 7075-T6 aluminum and then machined with our unique Double-Lug Picatinny recoil shoulders from the solid billet. We have designed and engineered the Double-Lug recoil system to allow the parallelism and perpendicularity of the lugs to the ring bore to be within .0002, thereby providing repeatability that no other mount in the world with similar integrated lugs has done before. The X-Rings are specifically designed for the Mil-STD 1913 rail system. Because of the Double-Lug system, they do require two (2) accompanied cross-slots in a 1913 cross-slot configuration. The ring caps are secured with Four (4) 8-32 x 1/2" Camcar-Textron Torx drive screws and with the same unique design that allows you to tighten the left side of the cap, then the right side without the scope rotating. The edges and corners are fully radiused, preventing snagging, and providing a beautiful appearance to your rifle. The rings are securely attached to your rail with an oversized clamp system using Two (2) 8-32 x 1/2" Camcar-Textron Torx screws, preventing any chance your rings will loosen or move once installed. With unparalleled precision and holding force, and sleek design, these will meet the extreme expectations of any class shooter. SPECS: 7075-T651 Aluminum Alloy, matte black, hard anodized to Mil-A-8625 standards. .700" (17.8mm) wide. Height measured from the top of base to center of the ring. 30mm - High: .1.075" (31.11mm).



## Attributes

- Name: [TPS PRODUCTS XRT ALUMINUM RINGS 30MM S-LOW](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100036960
- Mfr. No.: 52580
- Finish: Matte Blue
- Height: .820"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Super Low
- Style: Tactical Rings
- Delivery weight: 0.181kg
- Shipping height: 64mm
- Shipping width: 64mm
- Shipping length: 102mm

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide](#)
- [About Us](#)

# XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide

## Introduction

Thank you for choosing the XRT XRings Picatinny Scope Rings by TPS Products. This guide provides essential safety instructions and precautions to ensure the safe and effective use of your scope rings. Please read this guide carefully before installation and use.

## General Safety Guidelines

- Ensure the scope rings are compatible with your firearm and scope.
- Always follow the manufacturer's instructions for installation and use.
- Regularly inspect the scope rings for any signs of wear or damage.
- Store the scope rings in a dry and secure location when not in use.
- Keep the product out of reach of children and unauthorized users.

## Specific Safety Precautions for Use

- **Installation:**
  - Use only the recommended tools for installation to avoid damaging the screws or rings.
  - Ensure that the rings are securely fastened to prevent loosening during use.
- **Scope Alignment:**
  - Properly align the scope within the rings to maintain accuracy and prevent damage.
- **Weight Limitations:**
  - Do not exceed the weight limit of the scope rings as specified by the manufacturer.
- **Shooting Environment:**
  - Avoid using the scope rings in extreme weather conditions that may affect performance.
- **Maintenance:**
  - Regularly clean the scope rings according to the manufacturer's recommendations to prevent corrosion and ensure longevity.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools: a Torx screwdriver and any other recommended tools.
- Ensure you have a clean workspace free from obstructions.

### 2. Installation:

- Place the scope rings on the Picatinny rail system.
- Align the DoubleLug recoil shoulders with the crossslots on the rail.
- Secure the rings using the provided 832 x 1/2" CamcarTextron Torx screws. Tighten the screws evenly to avoid misalignment.
- Ensure the left side of the cap is tightened first, followed by the right side, to prevent scope rotation.

### 3. Scope Mounting:

- Insert the scope into the rings, ensuring it is level and correctly positioned.
- Tighten the ring caps securely, following the same tightening method as above.

#### **4. Final Checks:**

- Inspect the installation to ensure all screws are tight and the scope is properly aligned.
- Perform a function check to ensure the scope is securely mounted and does not shift during operation.

## **Disposal Instructions**

- Dispose of the product in accordance with local regulations regarding electronic waste and materials.
- Do not dispose of the product in household waste. Instead, take it to a designated recycling facility.

## **Contact Information for Further Support**

For any questions or concerns regarding the XRT XRings Picatinny Scope Rings, please refer to the manufacturer's website or contact the customer service department directly.

## **Conclusion**

By following these safety instructions and guidelines, you can ensure the safe and effective use of your XRT XRings Picatinny Scope Rings. Always prioritize safety and proper handling to enhance your shooting experience. Thank you for choosing TPS Products.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)