

AT OPTIC MOUNTS - BRAVO COMPANY BCM 1.93" AT OPTIC MOUNT FOR AIMPOINT MICRO T2

[Optics & Mounting](#) > [Electronic Sights](#) > [Mounting Hardware](#)

BCM® A/T™ Optic Mounts Capability in the face of the unexpected and catastrophic, the BCM A/T Mount is built in anticipation of a "no fail" shot that will save another human life. PERFORMANCE WITHOUT PEER Improving on Mil-Spec rail interfaces dating back over 30 years, the BCM A/T mount delivers unprecedented zero retention on a properly mounted red dot optic. Low profile and snag-free, BCM A/T Mounts are built with a minimal number of components - delivering a stronger component with less points of failure, ready to take on dynamic and adverse settings. Each A/T Mount features multiple integral recoil lugs to mitigate recoil and counter recoil to preserve your zero and ensure "no fail" shots are placed where intended by the trained rifleman. Starting at 2.15 oz, each 7075T6 billet mount is hard coat anodized per Mil-A-8625F. Additionally, both the steel alloy clamp and nut are hardened with Nitride coating. THE ANGLED TORQUE™ LOCK-UP A/T (Angled Torque) mounts employ angled torque through a patented* clamp which applies triangulating force to create a stronger and more reliable lock up of the mount onto the end user's rail. To retain the hardware in field conditions, this system uses a serrated locking spring-washer to prevent the loss of torque on the shaft nut. With an equivalent load applied, the A/T Mount delivers approximately twice the clamping force at the picatinny rail, versus a legacy horizontal interface. * US Patent D973.826, and other patents pending THE FLEET The A/T fleet is built optimized for both a variety of missions and proven red dot optics. Aimpoint® T-2, T-1 and CompM5 series: The Marksman lower 1/3 co-witness The Close Combat 1.93" Trijicon® MRO® The Marksman lower 1/3 co-witness The Close Combat 1.93" MADE IN AMERICA All BCM components and accessories unite state of the art manufacturing with lightweight and durable materials to ensure components that last a lifetime, performing far beyond performance requirements established nearly six decades ago. Aimpoint, T-2, T-1, CompM5 trademarks are property of Aimpoint Inc. Trijicon, MRO trademarks are property of Trijicon Inc.



Attributes

- Name: [BRAVO COMPANY BCM 1.93" AT OPTIC MOUNT FOR AIMPOINT MICRO T2](#)
- Manufacturer: [BRAVO COMPANY](#)
- Product no.: 430106544
- Mfr. No.: BCM-OM-AT-22
- Colour: Black
- Fits / Used For: Aimpoint Micro T1
- Height: 1.93"
- Delivery weight: 0.454kg
- Shipping height: 70mm
- Shipping width: 102mm
- Shipping length: 114mm
- UPC: 812526023841

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for AT OPTIC MOUNTS BRAVO COMPANY BCM 1.93" AT OPTIC MOUNT FOR AIMPOINT MICRO T2
- About Us

Safety Instruction Guide for AT OPTIC MOUNTS

BRAVO COMPANY BCM 1.93" AT OPTIC MOUNT

FOR AIMPOINT MICRO T2

Introduction

Thank you for choosing the BCM A/T™ Optic Mount. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read this document carefully before installation and usage.

General Safety Guidelines

- Ensure that the optic mount is compatible with your specific firearm and optic model.
- Always handle firearms and accessories with care and in accordance with local laws and regulations.
- Regularly inspect the mount for wear or damage before each use.
- Keep the mount and all related components out of reach of children and unauthorized users.
- In case of any malfunction or abnormal behavior, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

- Do not exceed the manufacturer's recommended torque specifications during installation.
- Ensure that the mount is securely attached to the rail before using the firearm.
- Avoid using the mount in excessively harsh environments without proper maintenance.
- Be aware of the potential for recoil and ensure that all components are properly secured to prevent dislodgment during use.
- If using the mount in adverse conditions, regularly check for any signs of damage or loosening.

Instructions for Installation and Usage

1. Installation:

- Clean the mounting surface of your firearm to remove any debris or oil.
- Align the BCM A/T Mount with the Picatinny rail on your firearm.
- Insert the clamp and nut in accordance with the provided specifications.
- Use a torque wrench to tighten the nut to the manufacturer's recommended torque settings.
- Verify that the mount is securely fastened and does not move.

2. Usage:

- Before each use, ensure that the optic is properly mounted and that all components are intact.
- Check the zero of your optic after installation and periodically during use.
- When not in use, store the firearm in a secure location to prevent unauthorized access.

Disposal Instructions

- Dispose of any packaging materials responsibly, in accordance with local waste disposal regulations.
- When the BCM A/T Mount reaches the end of its life cycle, dispose of it in a manner that complies with applicable environmental regulations.
- Recycle components where possible.

Contact Information for Further Support

For any inquiries regarding safety, usage, or installation of the BCM A/T™ Optic Mount, please refer to the manufacturer's website or contact your local distributor.

Please ensure that you adhere to these guidelines to promote safety and effective usage of your BCM A/T™ Optic Mount. Thank you for your attention to these important instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk