

HANNIBAL RAIL FOR RUGER® MINI-14® & RUGER® MINI THIRTY® - SAMSON MANUFACTURING CORP HANNIBAL RAIL FOR RUGER MINI-14 & THIRTY-2008/LATER GRAY

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

Complete your Ruger® Mini-14® , Mini Thirty® or Ruger® AC-556 with this precision machined direct optic mount solution from Samson. IMPORTANT: The Hannibal Rail is currently offered for 2008 and later Mini-14® or Mini Thirty®, or 2007 and earlier Mini-14® (in both black and natural gray). NOTE - It also fits on the Ruger AC-556. Refer to the Ruger® serial number lookup on their website if you are unsure what year your rifle was manufactured. It is very important that the correct combination of Hannibal Rail and barrel type is used. If during installation there are any fitment concerns, immediately stop and contact Samson Mfg. customer service. Choose 2008 and Later Mini-14® or Mini Thirty® (Black or Natural Gray) if your rifle has a factory flange barrel and a series number beginning with 580 and higher. Choose 2007 and Earlier Mini-14® ONLY (Black or Natural Gray) if your rifle has a factory straight pencil barrel and a series number beginning with 181 and higher, but not including 580 and higher. Directly mount a micro red dot forward of the action without the need for a Picatinny rail clamp adapter. The integrated Picatinny rail on top of the Hannibal Rail is perfect for mounting any accessory your heart desires, and gives your rifle a more tactical look. The included 2" Picatinny rail and QD swivel mount can be attached to the side of the Hannibal Rail for even more accessory mounting options. The Hannibal Rail accepts red dot optics compatible with the following footprints: Trijicon RMR® Leupold DeltaPoint® Pro Vortex VENOM® C-MORE NOTE: With the large number of micro red dots currently available on the market, along with any that may come out in the near future, it is impossible to guarantee that every single one will be compatible with the Hannibal Rail. Whether it's minor changes in the optic footprint, or differences in the optic mounting screw thread pitch, Samson Mfg. customer service will do everything they can to answer any compatibility questions you may be having. INCLUDES Hannibal rail Barrel clamp 2" Picatinny rail section QD swivel mount Blue thread locker SCREWS: 4X 10-32 x 3/8 low head screw (2X 2" picatinny rail section, 2X QD swivel mount) 4X 6-32 x 3/8 socket head screw (2X barrel clamp, 2X micro red dot optional) 2X MR1 pins (Trijicon RMR®, Leupold DeltaPoint® Pro) 2X MR2 pins (C-MORE, Vortex VENOM®) Hex Wrenches: 9/64" 7/64" 3/32" 1/16" FEATURES Compatible with Samson Mfg's A-TM Folding Stock (see IMPORTANT information above for Mini-14® and Mini Thirty® compatibility) Replaces factory plastic handguard Mounts directly to barrel, allowing the use of most aftermarket Mini-14® stocks Allows mounting of micro red dot Specifications: Material: 6061-T6 Aluminum Finish: Type III, class 2 anodized finish Length: 9.9" Width: 1.5" Height: 0.7" Weight: 5.6 oz. NOTE: OPTIC NOT INCLUDED



Attributes

- Name: [SAMSON MANUFACTURING CORP HANNIBAL RAIL FOR RUGER MINI-14 & THIRTY-2008/LATER GRAY](#)
- Manufacturer: [SAMSON MANUFACTURING CORP](#)
- Product no.: 430107460
- Mfr. No.: 03-00265-11
- Colour: Gray

- Length: 9.9"
- Material: Aluminum
- Model: Mini-30,Mini-14
- Style: Picatinny
- Weapon type: Ruger
- Delivery weight: 0.159kg
- Shipping height: 260mm
- Shipping width: 83mm
- Shipping length: 273mm
- UPC: 850028390252

Item details

Made in USA

US export classification: 0A501.y.1

Table of Contents

- [Startpage](#)
- [HANNIBAL RAIL FOR RUGER® MINI14® & RUGER® MINI THIRTY®](#)
- [About Us](#)

HANNIBAL RAIL FOR RUGER® MINI14® & RUGER® MINI THIRTY®

Consumer Safety Instruction Guide

Introduction

Thank you for choosing the Hannibal Rail for your Ruger® Mini14® or Mini Thirty®. This guide provides essential safety instructions and information to ensure the safe and effective use of the product. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure that the Hannibal Rail is compatible with your specific model of Ruger® Mini14® or Mini Thirty® before installation.
- Always handle firearms and firearm accessories responsibly and with care.
- Store the Hannibal Rail and all related components in a safe location, away from children and unauthorized users.
- Regularly inspect the Hannibal Rail for any signs of wear or damage before each use.
- Do not exceed the recommended weight limit for accessories mounted on the Hannibal Rail.

Specific Safety Precautions for Use

- Only use the Hannibal Rail with compatible optics and accessories as specified in the product description.
- Ensure that the firearm is unloaded before installing or adjusting the Hannibal Rail.
- Avoid using the Hannibal Rail in extreme weather conditions that may affect its performance.
- If you notice any unusual behavior or performance issues with the Hannibal Rail or your firearm, cease use immediately and consult a qualified gunsmith or customer service.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including the included hex wrenches (9/64", 7/64", 3/32", 1/16").
- Ensure that your firearm is unloaded and pointed in a safe direction.

2. Installation Steps:

- Identify the correct model of the Hannibal Rail based on your firearm's year of manufacture:
 - For 2008 and later Mini14® or Mini Thirty® with a factory flange barrel (series number 580 and higher), use the corresponding rail option.
 - For 2007 and earlier Mini14® with a factory straight pencil barrel (series number 181 and higher, but not including 580 and above), select the appropriate rail option.
- Attach the barrel clamp to the barrel of your firearm using the provided 632 x 3/8 socket head screws (2X).
- Secure the Hannibal Rail to the barrel clamp, ensuring it is firmly in place.
- If desired, attach the 2" Picatinny rail section and QD swivel mount to the side of the Hannibal Rail for additional accessory mounting options.
- Mount your chosen micro red dot optic on the integrated Picatinny rail, ensuring compatibility with the listed footprints (Trijicon RMR®, Leupold DeltaPoint® Pro, Vortex VENOM®, CMORE).
- Use the included MR1 and MR2 pins as necessary for securing optics (2X MR1 for Trijicon RMR® and Leupold DeltaPoint® Pro; 2X MR2 for CMORE and Vortex VENOM®).
- After installation, doublecheck all screws and connections to ensure everything is secure.

3. Usage:

- Once installed, aim to use the Hannibal Rail primarily for its intended purpose of mounting optics and accessories.
- Regularly check the tightness of all screws and mounts before each use.
- If you experience any fitment concerns during installation, stop immediately and contact customer service for assistance.

Disposal Instructions

- Dispose of the Hannibal Rail and any associated materials in accordance with local regulations.
- Avoid disposing of the product in regular household waste. Instead, consider recycling options for metal components, if available in your area.

Contact Information for Further Support

- For any questions, concerns, or compatibility inquiries, please reach out to customer service at Samson Manufacturing Corp for assistance.

Conclusion

We appreciate your commitment to safety and responsible firearm ownership. By following these guidelines and instructions, you can ensure the proper use of the Hannibal Rail for your Ruger® Mini14® or Mini Thirty®. Stay safe and enjoy your shooting experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk