

# **GAS BLOCK FRONT SIGHT RUGER® AC-556 STYLE - SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2007/EARLIER BLACK**

[Rifle Parts](#) > [Gas System Parts](#) > [Gas Blocks](#)

Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625"" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625"" diameter barrel and the new factory flanged .625"" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562"" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.



Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625"" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625"" diameter barrel and the new factory flanged .625"" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562"" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.

## **Attributes**

- Name: [SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2007/EARLIER BLACK](#)
- Manufacturer: [SAMSON MANUFACTURING CORP](#)
- Product no.: 430107467
- Mfr. No.: 02-00070-03
- Inside Diameter: .562
- Material: Stainless Steel
- Style: Screw
- Weapon type: AR-15
- Delivery weight: 0.113kg
- Shipping height: 29mm
- Shipping width: 127mm
- Shipping length: 127mm
- UPC: 850028390542

## **Item details**

Made in USA  
US export classification: 0A501.x

# Table of Contents

- Startpage
- Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE
- About Us

# Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE

## Introduction

Thank you for purchasing the GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE by Samson Manufacturing Corp. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of this product. Please read this document carefully before installation and use.

## General Safety Guidelines

- Ensure the product is compatible with your firearm before installation.
- Always handle firearms and accessories with care, following all safety protocols.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the product for any signs of wear or damage before use.
- In case of any safety concerns or product issues, cease use immediately and seek assistance.

## Specific Safety Precautions for Use

- Only use this gas block front sight with compatible Mini14® and Mini Thirty® rifles as specified.
- Ensure that the installation is performed by a qualified individual or gunsmith if you are not experienced.
- Do not modify the product in any way, as this may compromise safety and performance.
- Always wear appropriate safety gear, including eye protection, when handling firearms.
- Be aware of your surroundings and ensure a safe shooting environment.

## Instructions for Installation and Usage

### 1. Compatibility Check

- Verify that your rifle's barrel diameter and serial number prefix match the specifications provided.
- For Mini14® rifles manufactured in 2008 or later, ensure a factory flanged .625" diameter barrel.
- For Mini14® rifles manufactured in 2007 or earlier, ensure a factory straight pencil .562" diameter barrel.

### 2. Installation Steps

- Ensure the firearm is unloaded and pointed in a safe direction.
- Remove the existing gas block front sight if applicable.
- Align the new gas block front sight with the barrel, ensuring a secure fit.
- Use the appropriate screws to fasten the gas block front sight in place.
- Tighten screws to the manufacturer's recommended torque specifications.

### 3. PostInstallation Checks

- Inspect the installation to ensure that the gas block front sight is securely attached.
- Perform a function check of the firearm to ensure proper operation.

### 4. Usage Instructions

- Always follow standard firearm safety practices when using your rifle.
- Regularly check the gas block front sight for any signs of loosening or damage during use.

## **Disposal Instructions**

- When disposing of this product, follow local regulations regarding the disposal of firearms accessories.
- Ensure that the product is rendered unusable before disposal to prevent unauthorized use.

## **Contact Information for Further Support**

For any questions or concerns regarding the product, please refer to the manufacturer's website or customer support resources.

Please ensure that you keep this guide for future reference and share it with others who may use this product. Safety is a priority, and your adherence to these guidelines will help ensure a safe shooting experience.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)