

GAS BLOCK FRONT SIGHT RUGER® AC-556 STYLE - SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2008/LATER SS

[Rifle Parts](#) > [Gas System Parts](#) > [Gas Blocks](#)

Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625"" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625"" diameter barrel and the new factory flanged .625"" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562"" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.



Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625"" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625"" diameter barrel and the new factory flanged .625"" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562"" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.

Attributes

- Name: [SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2008/LATER SS](#)
- Manufacturer: [SAMSON MANUFACTURING CORP](#)
- Product no.: 430107468
- Mfr. No.: 02-00068-00
- Inside Diameter: .625
- Material: Stainless Steel
- Style: Screw
- Weapon type: AR-15
- Delivery weight: 0.113kg
- Shipping height: 127mm
- Shipping width: 140mm
- Shipping length: 51mm
- UPC: 850028390559

Item details

Made in USA
US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE
- About Us

Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE

Introduction

Thank you for choosing the GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE from SAMSON MANUFACTURING CORP. This product is designed for use with Mini14® and Mini Thirty® rifles that meet specific compatibility requirements. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that the product is compatible with your firearm model before installation.
- Always handle firearms with care and follow all safety protocols.
- Store this product in a safe location, away from children and unauthorized users.
- Regularly check for any signs of wear or damage to the gas block front sight.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about any product recalls or safety updates via the EU Safety Gate platform.

Specific Safety Precautions for Use

- Only use this product with Mini14® rifles manufactured in 2008 or later that have a factory flanged .625" diameter barrel, or Mini Thirty® rifles with compatible barrels.
- Avoid using this gas block front sight with Mini14® rifles that have a factory straight pencil .562" diameter barrel manufactured in 2007 or earlier, unless they meet the specified serial number prefixes.
- Always ensure that the firearm is unloaded before installation or adjustment of the gas block front sight.
- Wear safety glasses while installing or working on your firearm to protect against accidental injuries.
- Do not attempt to modify or alter the gas block front sight in any way.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is completely unloaded and safe to handle.
- Gather the necessary tools for installation, including a torque wrench and appropriate screwdrivers.

2. Installation Steps

- Remove the existing gas block front sight from your rifle by unscrewing it carefully.
- Align the new GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE with the barrel.
- Secure the gas block front sight using the provided screws. Ensure they are tightened to the manufacturer's specifications using a torque wrench.
- Check for proper alignment and functionality before using the firearm.

3. PostInstallation Check

- After installation, perform a function check to ensure the gas block front sight operates correctly.
- Inspect the installation for any signs of looseness or misalignment.

4. Usage

- Use the gas block front sight as intended, ensuring that it is properly aligned for accurate shooting.
- Regularly inspect the sight for any damage or wear during routine maintenance of your firearm.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the gas block front sight is no longer usable, dispose of it in a manner that prevents its use by unauthorized individuals.
- Recycle materials where possible, following local recycling guidelines.

Contact Information for Further Support

For any questions or concerns regarding the GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE, please refer to the manufacturer's contact information or consult your local firearms dealer for assistance.

By following these guidelines, you can help ensure the safe use of the GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE and maintain compliance with the EU General Product Safety Regulation. Thank you for prioritizing safety in your firearm practices.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk