

AK12 MUZZLE BRAKES - MIDWEST INDUSTRIES AK12 MUZZLE BRAKE - M24X1.5RH

[Rifle Parts](#) > [Muzzle Devices](#) > [Compensators & Muzzle Brakes](#)

Inspired by the AK12 design, Midwest has three Muzzle Devices, made in three different thread pitches. Single chamber design reduces muzzle climb
Constructed from tool steel with a phosphate finish Includes new crush washer
100% made in the U.S.A., MI Lifetime Warranty Made for thread pitches
M14X1LH / M24X1.5RH / 1/2X28



Attributes

- Name: [MIDWEST INDUSTRIES AK12 MUZZLE BRAKE - M24X1.5RH](#)
- Manufacturer: [MIDWEST INDUSTRIES](#)
- Product no.: 430107685
- Mfr. No.: MI-AK12MB-2
- Finish: Black
- Material: Steel
- Threads: M24x1.5
- Weapon type: AK-47
- Delivery weight: 0.454kg
- UPC: 812102034957

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for AK12 Muzzle Brake](#)
- [About Us](#)

Safety Instruction Guide for AK12 Muzzle Brake

Introduction

Thank you for choosing the AK12 Muzzle Brake by Midwest Industries. This product is designed to enhance your shooting experience by reducing muzzle climb and improving accuracy. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that you are familiar with the laws and regulations regarding firearm accessories in your region before purchasing or using this product.
- Always handle firearms and accessories with care, following proper safety protocols.
- Store the muzzle brake and all firearm accessories in a secure location, away from children and unauthorized users.
- Regularly inspect the muzzle brake for signs of wear or damage before each use.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always wear appropriate eye and ear protection while shooting.
- Ensure that the firearm is unloaded before installing or removing the muzzle brake.
- Do not use the muzzle brake with ammunition that exceeds the manufacturer's specifications.
- Avoid using the muzzle brake in conditions where it may become overheated, as this can lead to malfunction or injury.
- Be aware of your surroundings and ensure that you have a safe shooting environment.

Instructions for Installation and Usage

Installation

1. Ensure that the firearm is unloaded and pointed in a safe direction.
2. Remove the existing muzzle device, if applicable, using the appropriate tools.
3. Clean the threads of the barrel to remove any debris or old thread locker.
4. Align the muzzle brake with the threads of the barrel, ensuring that the correct thread pitch (M24x1.5RH) is used.
5. Handtighten the muzzle brake onto the barrel, ensuring it is secure.
6. Use a torque wrench to tighten the muzzle brake to the manufacturer's recommended specifications.
7. Install the new crush washer as provided, ensuring it is properly seated.
8. Check the alignment and security of the muzzle brake before use.

Usage

- After installation, test the muzzle brake at a shooting range to ensure proper functionality.
- Monitor the performance of the muzzle brake during use, and check for any signs of damage or wear.
- If you experience excessive recoil or noise, discontinue use and inspect the product.

Disposal Instructions

- Dispose of the AK12 Muzzle Brake according to local regulations for metal products.
- If the product is damaged or no longer usable, ensure it is properly recycled or disposed of in a safe manner.

Contact Information for Further Support

For any questions or concerns regarding the AK12 Muzzle Brake, please contact the manufacturer or refer to the product's official website for additional resources.

Thank you for prioritizing safety while using the AK12 Muzzle Brake. Your responsible handling and care of this product contribute to a safer shooting experience for everyone.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk