

SCT 43X SUB COMPACT STRIPPED POLYMER FRAME - SCT MANUFACTURING SCT 43X SC STRIPPED POLYMER FRAME FOR GLOCK 43X & 48 ODG

[Handgun Parts](#) > [Frame Parts](#) > [Frames](#)

The SCT Manufacturing Glock® Compatible Sub Compact stripped frame is going to change the way you build pistols. It is the only frame at this price point packed with this level of features. This is a serialized frame with shooter-oriented ergonomics. Polished stainless steel over molded rails provide the optimal platform that is ready to build. They are made with an industry leading proprietary polymer blend and compatible with Glock® 43X and 48 components. FEATURES Serrations and index point on trigger guard to help control recoil Serrations on top of beaver tail reduce glare Flared mag well Thumb Accelerator pad Advanced contour grip with aggressive texturing Modified Factory Picatinny with addition al mounting slot. Extended beaver tail with low profile bore axis Grip angle is the same as Glock® Slide stop guard Larger trigger guard for better access with gloves Recessed contoured mag release area for faster mag changes Compatible with compact 9mm Luger. Frame stripped assembly includes: SCT SC polymer frame, electroless nickel locking block. Disclaimer: SCT Manufacturing recommends the installation of mating components be performed by a certified gunsmith to ensure proper function and safety. Due to variations in third party parts and accessories, SCT Manufacturing will not be held liable for any damage caused to you and/or your firearm as a result of aftermarket accessory



Attributes

- Name: [SCT MANUFACTURING SCT 43X SC STRIPPED POLYMER FRAME FOR GLOCK 43X & 48 ODG](#)
- Manufacturer: [SCT MANUFACTURING](#)
- Product no.: 430107845
- Mfr. No.: 02-2502-01-00-I
- Capacity: 0-Round
- Cartridge: 380 Auto (ACP), 9 mm Luger
- Finish: Outdoor Green
- Length: 7"
- Model: 43X,48
- Style: Stripped
- Weapon type: Glock
- Weight: 1 lb
- Delivery weight: 0.454kg
- Shipping height: 76mm
- Shipping width: 152mm
- Shipping length: 254mm
- UPC: 850055982215

Item details

Made in USA
US export classification: 0A509.c

Table of Contents

- Startpage
- SCT 43X Sub Compact Stripped Polymer Frame Safety Instructions
- About Us

SCT 43X Sub Compact Stripped Polymer Frame Safety Instructions

Introduction

Thank you for choosing the SCT 43X Sub Compact Stripped Polymer Frame by SCT Manufacturing. This guide provides essential safety instructions to ensure the safe use and handling of your product. Please read this manual carefully before installation and usage.

General Safety Guidelines

- Always treat your firearm and its components as if they are loaded.
- Follow all local laws and regulations regarding firearm usage and ownership.
- Ensure that the firearm is stored securely and out of reach of children and unauthorized users.
- Inspect the frame and components for any signs of wear or damage before use.
- If you experience any issues or malfunctions, cease use immediately and consult a certified gunsmith.

Specific Safety Precautions for Use

- Ensure that you are using the frame with compatible Glock® components (Glock® 43X and 48).
- Be aware of the potential risks associated with firearm assembly and disassembly.
- Use appropriate protective gear, such as safety glasses and hearing protection, when handling firearms.
- Avoid using the firearm in wet or humid conditions to prevent damage to the frame and components.
- Do not exceed the manufacturer's recommended specifications for ammunition type and load.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and components for assembly.
- Ensure you are in a safe and secure environment for firearm assembly.

2. Assembly Instructions:

- Carefully read the user manual for the OEM trigger assembly and other components.
- Install the electroless nickel locking block into the frame.
- Insert the OEM trigger assembly, ensuring it is properly seated.
- Attach the standard polymer magazine catch and spring.
- Secure the steel trigger pin and locking block pin.
- Install the standard OEM slide lock and its coil spring.
- Insert the polymer trigger housing pin and ensure the OEM trigger housing with ejector is properly positioned.
- Attach the standard slide stop assembly.

3. Final Checks:

- Once assembled, perform a thorough inspection to ensure all components are secure and functioning properly.
- Test the frame's functionality with dummy rounds before livefire testing.

4. Usage Instructions:

- Load the firearm only when you are ready to use it.

- Always point the firearm in a safe direction.
- Keep your finger off the trigger until ready to shoot.
- Follow all range safety protocols when using the firearm at a shooting range.

Disposal Instructions

- Dispose of any damaged or worn components in accordance with local regulations.
- Do not discard the frame or its components in regular household waste.
- Contact your local waste management authorities for guidance on safe disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the SCT 43X Sub Compact Stripped Polymer Frame, please refer to the manufacturer or your point of purchase for assistance. It is important to have a reliable source for support and information regarding your product.

Conclusion

The SCT 43X Sub Compact Stripped Polymer Frame is designed with safety and functionality in mind. By following these guidelines and instructions, you can ensure a safe and enjoyable experience with your firearm. Always prioritize safety and responsibility when handling firearms. Thank you for choosing SCT Manufacturing.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk