

LIBERATOR II MINI RED DOT SIGHT - SWAMPFOX OPTICS

LIBERATOR II 1X22MM RED MULTI-RETICLE RED DOT BLACK

[Optics & Mounting](#) > [Electronic Sights](#) > [Red Dot Sights](#)

Liberator II keeps everything we liked about the original Liberator, while stuffing the inside with upgraded technology, like new emitters with greatly improved battery life and Shake 'N Wake motion sensing auto on/off. The first two brightness settings are night vision compatible, with the following 8 further settings daylight visible. Liberator II ships with two 1913 MIL-STD Picatinny mounts for use on a variety of platforms and the scope body is compatible with industry standard micro dot mounts. Small and light but tough, Liberator II is rated for 800 Gs of shock, so it's a great fit for 12 gauge shotguns and .308 rifles. Liberator II is waterproof, fog resistant and features hydrophobic & anti-scratch coatings on the anti-glare lenses.



Attributes

- Name: [SWAMPFOX OPTICS LIBERATOR II 1X22MM RED MULTI-RETICLE RED DOT BLACK](#)
- Manufacturer: [SWAMPFOX OPTICS](#)
- Product no.: 430108022
- Mfr. No.: RDLR122-2MR
- Battery Life: 25000 hours
- Brightness Settings: 10 settings
- Click Value: -
- Finish: Black
- Night Vision Compatible: Yes
- Night Vision Compatible: Yes
- Power Supply: CR 2032
- Reticle: Multi-Reticle System
- Sight Type: Red Dot
- Weight: 0.22 lbs
- Delivery weight: 0.34kg
- Shipping height: 127mm
- Shipping width: 95mm
- Shipping length: 83mm
- UPC: 889157002767

Item details

US export classification: 0A504.c

Table of Contents

- Startpage
- Safety Instruction Guide for LIBERATOR II MINI RED DOT SIGHT
- About Us

Safety Instruction Guide for LIBERATOR II MINI RED DOT SIGHT

Introduction

Thank you for choosing the LIBERATOR II MINI RED DOT SIGHT by SWAMPFOX OPTICS. This guide provides essential safety instructions and information to ensure the safe and effective use of your red dot sight. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that all users are familiar with the operation of the LIBERATOR II MINI RED DOT SIGHT.
- Always inspect the sight for any damage before use. Do not use if damaged.
- Keep the sight out of reach of children and unauthorized users.
- Use the sight only for its intended purpose: as a firearm accessory.
- Always follow local laws and regulations regarding the use of firearm accessories.
- Store the sight in a safe, dry place when not in use to prevent damage.

Specific Safety Precautions for Use

- **Shock Resistance:** The LIBERATOR II is rated for 800 Gs of shock. Ensure that it is securely mounted on your firearm to prevent accidental dislodging.
- **Waterproof and Fog Resistant:** Although the sight is waterproof and fog resistant, avoid exposing it to extreme conditions for prolonged periods.
- **Battery Safety:**
 - Use only the specified battery type (CR 2032).
 - Do not attempt to open or modify the battery compartment.
 - Dispose of used batteries according to local regulations.
- **Night Vision Compatibility:** The first two brightness settings are night vision compatible. Ensure the appropriate setting is used based on lighting conditions.
- **Coatings and Lenses:** The sight features hydrophobic and antiscratch coatings. Avoid using abrasive materials for cleaning the lenses.

Instructions for Installation and Usage

Installation

1. Mounting the Sight:

- Use the provided 1913 MILSTD Picatinny mounts for installation.
- Ensure the sight is securely fastened to the firearm's rail system.
- Confirm that the sight is level and properly aligned before tightening the mount screws.

2. Battery Installation:

- Open the battery compartment using a suitable tool if needed.
- Insert the CR 2032 battery, ensuring correct polarity (+ and -).
- Close the battery compartment securely.

Usage

1. Powering On/Off:

- The sight features Shake 'N Wake motion sensing technology. It will automatically turn on with movement and turn off after a period of inactivity.
- To manually turn the sight on or off, press the designated button.

2. Adjusting Brightness:

- Use the brightness adjustment buttons to select from the 10 available settings.
- Ensure the brightness is set according to the ambient lighting conditions for optimal visibility.

3. Zeroing the Sight:

- Follow the specific zeroing instructions provided by your firearm manufacturer.
- Make adjustments to the windage and elevation knobs as needed to align the reticle with your point of aim.

Disposal Instructions

- Dispose of the LIBERATOR II MINI RED DOT SIGHT and its components in accordance with local regulations.
- Do not dispose of electronic devices in regular household waste.
- Remove the battery before disposal and recycle it according to local battery recycling guidelines.

Contact Information for Further Support

For any questions regarding the LIBERATOR II MINI RED DOT SIGHT, please refer to the manufacturer's website or customer support resources. It is essential to have an EUbased contact for safety inquiries.

Conclusion

By following these safety instructions, you can ensure the safe and effective use of your LIBERATOR II MINI RED DOT SIGHT. Always prioritize safety and compliance with local regulations when using firearm accessories. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk