

BRN-22 EXTRACTOR PLUNGER - BROWNELLS BRN-22 EXTRACTOR PLUNGER

[Home](#)

BRN-22 replacement extractor plunger. Extractor plunger is backwards compatible with standard Ruger® 10/22® bolts. Extractor plunger is made from 420 stainless steel, then ground and polished for smooth operation.



Attributes

- Name: [BROWNELLS BRN-22 EXTRACTOR PLUNGER](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 430109578
- Mfr. No.: AZTP-22-00-008
- Model: BRN-22
- Weapon type: Brownells
- Delivery weight: 0.045kg
- Shipping height: 3mm
- Shipping width: 3mm
- Shipping length: 3mm
- UPC: 050806001237

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- BRN22 Extractor Plunger Safety Instruction Guide
- About Us

BRN22 Extractor Plunger Safety Instruction Guide

Introduction

Thank you for choosing the BRN22 Extractor Plunger from Brownells. This guide provides important safety information and instructions to ensure the safe use of this product. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure that the BRN22 Extractor Plunger is only used with compatible Ruger® 10/22® bolts.
- Always handle the extractor plunger with care to avoid injury.
- Keep the extractor plunger out of reach of children and vulnerable individuals.
- Regularly inspect the extractor plunger for any signs of damage or wear.
- If the extractor plunger appears damaged, do not use it and seek a replacement.
- Follow all local laws and regulations regarding firearm parts and accessories.

Specific Safety Precautions for Use

- Only use the extractor plunger in a welllit and safe environment.
- Wear appropriate safety gear, such as safety glasses, when handling the extractor plunger.
- Ensure that the firearm is unloaded before installing or replacing the extractor plunger.
- Avoid using excessive force during installation to prevent damage to the extractor plunger or firearm.
- If you are unsure about the installation process, consult a qualified gunsmith.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is completely unloaded and pointed in a safe direction.
- Gather necessary tools, such as a punch tool and hammer.

2. Installation Steps

- Remove the existing extractor plunger from the Ruger® 10/22® bolt, if applicable.
- Align the BRN22 Extractor Plunger with the bolt.
- Gently press the extractor plunger into place using a punch tool.
- Ensure that the extractor plunger is seated properly and functions smoothly.
- Reassemble the bolt and reinstall it into the firearm.

3. PostInstallation Check

- After installation, perform a function check to ensure the extractor plunger operates correctly.
- Test the firearm in a safe environment to confirm proper operation.

Disposal Instructions

- Dispose of the extractor plunger responsibly, following local regulations for metal and firearm parts.
- Do not dispose of the extractor plunger in regular household waste.

Contact Information for Further Support

For any questions or concerns regarding the BRN22 Extractor Plunger, please refer to the manufacturer's website or contact their customer support for assistance.

By following these safety instructions, you can ensure a safe and effective experience with the BRN22 Extractor Plunger. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk