

L89 DRIVE LOCK M-LOK RAIL - SONS OF LIBERTY GUN WORKS L89 DRIVE LOCK 9.75" M-LOK RAIL W/STEEL QD SOCKETS FOR AR15

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

The L89 handguard takes what makes the M89 handguard a best-in-class product and elevates it even further. Featuring a Titanium barrel nut, 7 sided M-LOK attachment slots, two integrated steel QD (limited Rotation) sockets, and maximized cooling slots beneath the 12 o'clock rail, the L89 is built for end-users who require every little bit of mounting space they can get. Built on the M89/Driveloack lockup system, the L89 incorporates valued end user feedback in getting the most utility possible out of a handguard in modern combat applications. Maximum strength, maximum mounting space, and weight savings material choices make this one of the finest fighting handguards available to date. Available Lengths: 9.75" 10.75" 13.75" Finish: Mil-Spec MIL-A-8625F, Type III, Class 2, Hard Anodized Coating, Non-Reflective, NiAc Seal (Anodized to match SOLGW receivers) What's included: L89 Rail Titanium Barrel Nut Barrel Nut Wrench Lock-Up Components KEY FEATURES: 7 sided MLOK Integrated limited rotation steel QD sockets Titanium Barrel Nut Cable optimized 12 o'clock 1913 rail - cooling slots and 1913 rail slots modified for maximum cable management options



Attributes

- Name: [SONS OF LIBERTY GUN WORKS L89 DRIVE LOCK 9.75" M-LOK RAIL W/STEEL QD SOCKETS FOR AR15](#)
- Manufacturer: [SONS OF LIBERTY GUN WORKS](#)
- Product no.: 430110641
- Mfr. No.: L89-9.75
- Colour: Black
- Length: 9.75"
- Material: Aircraft Aluminum
- Type: Tactical
- Weapon type: AR-15
- Delivery weight: 0.68kg
- Shipping height: 76mm
- Shipping width: 76mm
- Shipping length: 432mm
- UPC: 644625010503

Item details

Made in USA
US export classification: 0A501.y.1

Table of Contents

- Startpage
- L89 DRIVE LOCK MLOK RAIL SAFETY INSTRUCTION GUIDE
- About Us

L89 DRIVE LOCK MLOK RAIL SAFETY INSTRUCTION GUIDE

Introduction

Thank you for choosing the L89 DRIVE LOCK MLOK RAIL from SONS OF LIBERTY GUN WORKS. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your new handguard. Please read this document thoroughly before installation and use.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as outlined in this manual.
- Always wear appropriate protective gear, including safety glasses and gloves, when handling and installing the handguard.
- Inspect the product for any damage or defects before use. Do not use if damaged.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about recall updates via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Installation Precautions:**
 - Ensure the firearm is unloaded before installation.
 - Use the provided tools and components as specified in this guide.
- **Operational Safety:**
 - Always follow firearm safety rules when handling your AR15.
 - Regularly check the stability and integrity of the handguard during use.
- **Environmental Considerations:**
 - Avoid exposing the product to extreme temperatures, moisture, or corrosive environments.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools: L89 Rail, Titanium Barrel Nut, Barrel Nut Wrench, and LockUp Components.
- Ensure your workspace is clean and welllit.

2. Installation Steps:

- **Step 1:** Remove the existing handguard from your AR15.
- **Step 2:** Install the Titanium Barrel Nut onto the upper receiver of the firearm.
- **Step 3:** Use the Barrel Nut Wrench to securely tighten the barrel nut according to the manufacturer's specifications.
- **Step 4:** Align the L89 Rail with the mounting points and secure it using the LockUp Components.
- **Step 5:** Verify that all components are securely fastened and that the handguard is stable.

3. Usage Guidelines:

- Utilize the 7 sided MLOK attachment slots for mounting accessories as needed.
- Take advantage of the integrated limited rotation steel QD sockets for sling attachment.
- Ensure that cooling slots are unobstructed to maintain optimal performance.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the product in regular household trash.
- Consider recycling options where available.

Contact Information for Further Support

For questions or concerns regarding the L89 DRIVE LOCK MLOK RAIL, please refer to the manufacturer's website or customer support resources.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities. Enjoy your new L89 DRIVE LOCK MLOK RAIL!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk