

# COMPLETE SLIDE ASSEMBLIES FOR GLOCK 17® - BROWNELLS

## COMPLETE SLIDE ASSEMBLY WITH THREADED BARREL FOR GLOCK 17

[Handgun Parts](#) > [Slide Parts](#) > [Slides](#)

Complete Upper Assembly for Upgrading Your Factory G17 or a Custom Build  
Top off your next custom pistol build or upgrade with our Complete RMR Slide Assembly for Glock® 17 Gen3, available in three configurations. You can get your slide with a premium match-quality barrel, a ½"-28 tpi threaded barrel to accept a sound suppressor, or with a ported barrel that vents through a window in the top of the slide to counteract muzzle rise and help you keep the sights on the target for subsequent shots. This eliminates the need to install a bulky compensator on the muzzle, which means your new comped pistol will still fit standard holsters for the Glock® 17. These slides come fully assembled with the barrel and all the internal small parts installed, making this RMR Slide the ideal upgrade for your factory Glock® 17 Gen3 pistol or the perfect "top half" for a brand-new custom gun built on a compatible frame from another manufacturer. It features a pre-cut slot for easy, secure, low-profile mounting of a reflex red dot sight that fits the Trijicon RMR footprint. If you're not mounting a red dot at the moment, we've included a lightweight reinforced polymer cover plate to neatly fill the slot. Our RMR Slide comes with standard-height front and rear sights, which can serve as your primaries or a backup "iron" sights when paired with a red dot sight. Comes COMPLETE with barrel, front & rear sights, and small parts installed Fits Gen3 Glock® 17 pistols & clones Built-in mounting slot for reflex sights with the Trijicon RMR footprint Optic slot cover plate & recoil spring assembly also included Slide machined from 416 stainless steel billet, with a Black Nitride finish Choice of Solid top slide with standard barrel or ½"-28 tpi threaded barrel, OR distinctive top Window slide with ported/compensated barrel Each RMR Slide for Glock® starts life as a billet of 416 stainless steel that is machined to Glock® factory specifications inside, with a tough, extremely wear-resistant black Nitride finish. This slide fits standard Glock® factory G17 frames and compatible aftermarket frames. The match-quality barrel is machined from premium 416R stainless steel alloy. The muzzle of the threaded barrel has standard ½"-28 tpi threads. The ported barrel has eight ports angled to provide just the right counterforce to muzzle rise. On the sides at the rear, you'll find distinctive wide, shallow cocking serrations that give excellent "purchase" to rack the slide, plus a mirrored set of serrations up front that aid in manipulating the slide to press-check the chamber. Both sets of serrations make it easy to manipulate your pistol's slide from any angle and in any position. Hey, we have to admit these serrations just look very cool, too! Whether you're assembling a custom pistol to meet specific needs, or you're upgrading a factory Glock 17 for enhanced performance and versatility, a Brownells complete slide assembly is helps you complete your project quickly and easily! Brownells Gun Tech™ Note: Channel liner required for these slides. Channel liner is a press fit and requires a tool to install. We recommend #777-100-017.

NO IMAGE  
AVAILABLE

### Attributes

- Name: [BROWNELLS COMPLETE SLIDE ASSEMBLY WITH THREADED BARREL FOR GLOCK 17](#)
- Manufacturer: [BROWNELLS](#)

- Product no.: 430111300
- Mfr. No.: G17-SATB
- Cartridge: 9 mm Luger
- Finish: Black
- Model: 17
- Sights: RMR
- Style: Assembled
- Weapon type: Glock
- Delivery weight: 0.454kg
- UPC: 050806001541

## **Item details**

Made in USA

US export classification: 0A501.c

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for COMPLETE SLIDE ASSEMBLIES FOR GLOCK 17](#)
- [About Us](#)

# Safety Instruction Guide for COMPLETE SLIDE ASSEMBLIES FOR GLOCK 17

## Introduction

Thank you for choosing the COMPLETE SLIDE ASSEMBLIES FOR GLOCK 17 from Brownells. This guide provides essential safety instructions, general guidelines, and specific precautions to ensure the safe and effective use of your new slide assembly. Please read this document carefully before installation and usage.

## General Safety Guidelines

- Ensure that the slide assembly is compatible with your Glock 17 model before installation.
- Always handle firearms and firearm components with care. Treat every firearm as if it is loaded.
- Keep the slide assembly and all firearm components out of reach of children and unauthorized persons.
- Regularly inspect your firearm and its components for signs of wear or damage.
- Use only highquality ammunition that is compatible with your firearm.
- Always wear appropriate eye and ear protection when using firearms.
- Be aware of your surroundings and ensure a safe shooting environment.
- In case of any malfunction, cease use immediately and seek professional assistance.

## Specific Safety Precautions for Use

- Before installing the slide assembly, ensure that the firearm is unloaded and the magazine is removed.
- Avoid placing your fingers inside the trigger guard when handling the firearm.
- Do not attempt to modify or alter the slide assembly in any way, as this may compromise safety and performance.
- Ensure that the reflex sight is securely mounted and properly calibrated before use.
- Be cautious when using the threaded barrel with a suppressor; ensure that the suppressor is correctly attached and functioning.
- The ported barrel is designed to reduce muzzle rise; however, always maintain a firm grip on the firearm during use.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools for installation, including a channel liner installation tool (recommended: #777100017).
- Ensure a clean and welllit workspace.

### 2. Installation:

- Ensure the firearm is unloaded and the magazine is removed.
- Remove the existing slide from the Glock 17 frame.
- Install the channel liner in the slide assembly as per the tool instructions.
- Align the slide assembly with the frame and gently slide it into place.
- Ensure that the slide is fully seated and operates smoothly.

### 3. Mounting a Reflex Sight:

- If using a reflex sight, remove the cover plate from the mounting slot.
- Align the sight with the precut slot and secure it according to the manufacturer's instructions.

#### **4. Final Check:**

- After installation, conduct a function check to ensure that the slide cycles properly and that all components are secure.
- If any issues are detected, do not use the firearm until resolved.

## **Disposal Instructions**

- Dispose of the slide assembly and any associated components in accordance with local regulations.
- Do not dispose of firearms or firearm components in regular household waste.
- Contact local authorities or waste management facilities for proper disposal methods.

## **Contact Information for Further Support**

For any inquiries or support regarding the COMPLETE SLIDE ASSEMBLIES FOR GLOCK 17, please refer to the manufacturer's contact information provided with your purchase.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priorities. Enjoy your shooting experience responsibly!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)