

FHD FLASH HIDERS - REARDEN MANUFACTURING GROUP LLC FHD FLASH HIDER 1/2-28 TAPER SHOULDER BLACK NITRIDE

[Rifle Parts](#) > [Muzzle Devices](#) > [Flash Hiders](#)

FHD FLASH HIDERS These fit the plan B type mounts. This is an updated version that has larger wrench flats on the rear. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 30 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH H900 Atlas and Atlas XL Compatible Plan B Compatible Atlas XL Adapter No Overrun Black Nitride Finish (67 HRC Surface Hardness) Shims Not Included, if you would like to specifically time this, shims will be required. Note: your barrel may require a shim if the manufacturer did not put a thread relief on it.



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC FHD FLASH HIDER 1/2-28 TAPER SHOULDER BLACK NITRIDE](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111352
- Mfr. No.: 10079
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: 1/2-28
- Delivery weight: 0.227kg
- UPC: 850035804780

Item details

Made in USA

Table of Contents

- Startpage
- FHD Flash Hiders Safety Instruction Guide
- About Us

FHD Flash Hiders Safety Instruction Guide

Introduction

Thank you for choosing the FHD Flash Hider by Rearden Manufacturing Group LLC. This guide provides essential safety instructions and information to ensure the safe and effective use of your product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Product Safety:
 - Ensure safe use of the FHD Flash Hider, which is designed for firearms.
 - Follow all safety instructions to minimize risks associated with firearm accessories.
- Enhanced Recalls:
 - Be aware of any product recalls. Check the EU Safety Gate platform for updates and information on safety recalls.
- Online Shopping:
 - When purchasing online, ensure that the seller meets all safety requirements.
- Special Consumer Focus:
 - This product is intended for adult use only. Keep out of reach of children.
- EU Contact Point:
 - For safety inquiries, please refer to the contact information provided by your retailer or manufacturer.
- Rapid Alerts:
 - Stay informed about potential hazards through the EU Safety Gate system.

Specific Safety Precautions for Use

- Always use an alignment rod to ensure proper setup of the muzzle device and silencer.
- Ensure all surfaces are clean before installation.
- Torque the muzzle device to approximately 30 ftlbs and ensure it is square against the shoulder.
- When attaching the suppressor, torque it to 10 ftlbs and ensure proper alignment.
- Avoid using the FHD Flash Hider with Q cans, as this may void your warranty.
- The nitride finish contributes to a tighter seal; therefore, proper installation is crucial.
- If your barrel does not have a thread relief, a shim may be required for proper fitment.
- Check for any visible damage or wear before each use. If damaged, do not use the product.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools: alignment rod, torque wrench, and cleaning materials.
- Ensure your work area is clean and free from distractions.

2. Installation Steps:

- Clean the muzzle area of your firearm to remove any debris or oil.
- Align the FHD Flash Hider with the muzzle of the firearm.
- Use the alignment rod to confirm proper alignment.
- Torque the muzzle device to approximately 30 ftlbs, ensuring it is square against the shoulder.
- If required, install shims to time the muzzle device correctly.
- Attach the suppressor by screwing it onto the muzzle device. Torque to 10 ftlbs.
- Check alignment once more before finalizing the installation.

3. Post Installation:

- Inspect the installation to ensure everything is secure.
- Confirm that there are no obstructions to the threads or taper.
- Test the setup in a safe environment before regular use.

Disposal Instructions

- Dispose of the FHD Flash Hider in accordance with local regulations.
- Do not dispose of the product in household waste. Instead, take it to a designated recycling or hazardous waste facility.
- Ensure that any firearm accessories are disposed of safely to prevent accidents.

Contact Information for Further Support

For any questions or concerns regarding the FHD Flash Hider, please refer to the contact information provided by your retailer or visit the manufacturer's website for additional resources.

By following these safety instructions, you can ensure the safe and effective use of your FHD Flash Hider. Always prioritize safety and compliance with local laws and regulations. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk