

FHD FLASH HIDERS - REARDEN MANUFACTURING GROUP LLC FHD FLASH HIDER 1/2-36 SQUARE SHOULDER BLACK NITRIDE

[Rifle Parts](#) > [Muzzle Devices](#) > [Flash Hiders](#)

FHD FLASH HIDERS These fit the plan B type mounts. This is an updated version that has larger wrench flats on the rear. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 30 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH H900 Atlas and Atlas XL Compatible Plan B Compatible Atlas XL Adapter No Overrun Black Nitride Finish (67 HRC Surface Hardness) Shims Not Included, if you would like to specifically time this, shims will be required. Note: your barrel may require a shim if the manufacturer did not put a thread relief on it.



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC FHD FLASH HIDER 1/2-36 SQUARE SHOULDER BLACK NITRIDE](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111354
- Mfr. No.: 10179
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: 1/2-36
- Delivery weight: 0.227kg
- UPC: 850041491783

Item details

Made in USA

Table of Contents

- Startpage
- FHD Flash Hiders Safety Instruction Guide
- About Us

FHD Flash Hiders Safety Instruction Guide

Introduction

Thank you for purchasing the FHD Flash Hider from Rearden Manufacturing Group LLC. This guide provides important safety information and instructions for the correct installation and usage of your flash hider. Please read this guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- **Product Safety:** Ensure safe usage of the FHD Flash Hider, which is designed to comply with EU safety standards.
- **Enhanced Recalls:** Be aware that if any safety issues arise, standardized recall notices will be issued, and free remedies will be provided for dangerous products.
- **Online Shopping Protections:** If you purchased this product online, you have the same safety protections as if you bought it in a physical store.
- **Special Consumer Focus:** Extra precautions are in place to protect vulnerable groups, including children. This product is not intended for use by individuals under the age of 18.
- **EU Contact Point:** For any safety inquiries regarding this product, please refer to the designated EU contact point provided at the time of purchase.
- **Rapid Alerts:** Stay informed about any updates on unsafe products through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Proper Installation:** Always ensure the FHD Flash Hider is properly installed to prevent accidents or malfunctions.
- **Torque Specifications:**
 - Torque the muzzle device to approximately 30 ftlbs.
 - Torque the suppressor to 10 ftlbs.
- **Alignment:** Always use an alignment rod to ensure that the entire system is set up correctly.
- **Surface Preparation:** Ensure all surfaces are cleaned before installation. The muzzle device should be square against the shoulder.
- **Use of Rockset:** Always use Rockset to secure the muzzle device to the barrel properly.
- **Warranty Notice:** Using this product on a Q can void your warranty.
- **Inspection:** Regularly inspect the flash hider and associated components for wear or damage.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including an alignment rod, torque wrench, and cleaning supplies.
- Ensure your workspace is clean and welllit.

2. Installation Steps:

- Clean the muzzle device and ensure all threads and tapers are free from debris.
- Align the FHD Flash Hider with the muzzle device.
- Using a torque wrench, tighten the muzzle device to approximately 30 ftlbs.
- Apply Rockset to secure the muzzle device to the barrel.
- Ensure the flash hider is square against the shoulder.
- Torque the suppressor to 10 ftlbs.

3. Final Checks:

- Doublecheck the alignment and torque settings.
- Ensure that the installation is secure before using the firearm.

4. Usage:

- Follow all local laws and regulations regarding the use of flash hiders.
- Always handle firearms safely and responsibly.

Disposal Instructions

- Dispose of the FHD Flash Hider in accordance with local regulations.
- Do not dispose of in regular household waste. Check with local authorities for proper disposal methods.

Contact Information for Further Support

For further assistance or inquiries regarding safety concerns, please refer to the contact information provided at the time of purchase.

Thank you for your attention to these safety guidelines. By following these instructions, you can ensure the safe and effective use of your FHD Flash Hider. Enjoy your product responsibly!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk