

SPB MUZZLE BRAKES - REARDEN MANUFACTURING GROUP LLC

SPB MUZZLE BRAKE 0.375 9/16-24 THREADS SQUARE SHOULDER BLACK

[Rifle Parts](#) > [Muzzle Devices](#) > [Compensators & Muzzle Brakes](#)

SPB MUZZLE BRAKES These fit the plan B type mounts. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 15-25ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH H900 Atlas and Atlas XL Compatible Plan B Compatible Atlas Adapter Overrun Approximately 1.050" Atlas XL Adapter No Overrun Black Nitride Finish (67 HRC Surface Hardness) Shims Included* EXCEPT *Shims not included with the SR25/M110 or 11/16×24



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC SPB MUZZLE BRAKE 0.375 9/16-24 THREADS SQUARE SHOULDER BLACK](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111364
- Mfr. No.: 10141
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: 9/16-24
- Delivery weight: 0.227kg
- UPC: 850041491417

Item details

Made in USA

Table of Contents

- Startpage
- SPB Muzzle Brake Safety Instruction Guide
- About Us

SPB Muzzle Brake Safety Instruction Guide

Introduction

Thank you for choosing the SPB Muzzle Brake by Rearden Manufacturing Group LLC. This guide provides essential safety instructions and guidelines to ensure the proper and safe use of your muzzle brake. Please read this document thoroughly before installation and use.

General Safety Guidelines

- Ensure that all safety precautions are followed to prevent accidents and injuries.
- Product safety is paramount; always check for any recalls or safety notices related to your product.
- When shopping online, ensure that you are purchasing from a reputable source that complies with safety regulations.
- Extra caution should be taken if the product is being used around vulnerable groups, such as children.
- Always report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always use an alignment rod to ensure proper setup of the muzzle brake with your firearm.
- Ensure that all surfaces are clean before installation.
- The muzzle device must be properly torqued and secured using Rockset to the barrel.
- Using the muzzle brake on a Q can may void your warranty; proceed with caution.
- Torque the muzzle device to approximately 1525 ft lbs for secure installation.
- Ensure that the muzzle device is square against the shoulder to prevent misalignment.
- When attaching the silencer, ensure that the threads and tapers are clean to avoid damage.
- Torque the suppressor to 10 ft lbs to ensure proper fit and alignment.
- The nitride finish enhances sealing; however, proper torque and Rockset application are crucial.
- Always inspect the muzzle brake and related components for wear or damage before use.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including an alignment rod, torque wrench, and cleaning supplies.
- Ensure that your workspace is clean and welllit.

2. Cleaning:

- Clean the barrel and muzzle device thoroughly to remove any debris or oil.
- Use a suitable cleaning solvent and a cloth to wipe down all surfaces.

3. Installation:

- Align the muzzle brake with the barrel using the alignment rod.
- Carefully slide the muzzle brake onto the barrel, ensuring it is square against the shoulder.
- Securely torque the muzzle device to 1525 ft lbs using the torque wrench.
- Apply Rockset according to the manufacturer's instructions to secure the muzzle device.

4. Attaching the Silencer:

- Ensure that the threads and tapers on both the muzzle device and silencer are clean.
- Carefully screw on the silencer and torque it to 10 ft lbs.
- Doublecheck alignment to ensure proper fit.

5. Final Inspection:

- Inspect the installation to ensure everything is secure and properly aligned.
- Perform a function check of the firearm to ensure safe operation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- If the muzzle brake becomes damaged or is no longer usable, follow local guidelines for disposing of metal products.
- Do not dispose of the product in regular household waste if it is classified as hazardous.

Contact Information for Further Support

For any questions or concerns regarding the SPB Muzzle Brake, please refer to the manufacturer's contact details provided with your product. It is essential to reach out for assistance if you encounter any issues or require further clarification on safety practices.

Thank you for prioritizing safety and compliance while using the SPB Muzzle Brake. Your careful attention to these guidelines will help ensure a safe and enjoyable experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk