

RPB MUZZLE BRAKES - REARDEN MANUFACTURING GROUP LLC

RPB MUZZLE BRAKE 0.375 14X1 LH THREADS SQUARE SHOULDER BLACK

[Rifle Parts](#) > [Muzzle Devices](#) > [Compensators & Muzzle Brakes](#)

RPB MUZZLE BRAKES These fit the plan B type mounts. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 30 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH H900 Atlas and Atlas XL Compatible Plan B Compatible Atlas Adapter Overrun Approximately 1.050" Atlas XL Adapter No Overrun Nitride Shims Included



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC RPB MUZZLE BRAKE 0.375 14X1 LH THREADS SQUARE SHOULDER BLACK](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111369
- Mfr. No.: 10048
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: M14x1LH
- Delivery weight: 0.227kg
- UPC: 850035804476

Item details

Made in USA

Table of Contents

- Startpage
- RPB Muzzle Brake Safety Instruction Guide
- About Us

RPB Muzzle Brake Safety Instruction Guide

Introduction

Thank you for choosing the RPB Muzzle Brake from Rearden Manufacturing Group LLC. This product is designed to enhance the performance of your firearm while ensuring safety and reliability. Please read this safety instruction guide carefully to ensure proper use and maintenance of your muzzle brake.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the RPB Muzzle Brake in accordance with all safety standards. Follow all instructions to minimize risks.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices related to this product. You can find updates on the EU Safety Gate platform.
- **Online Shopping Protections:** If you purchased this product online, ensure that the retailer complies with safety regulations.
- **Special Consumer Focus:** This product is not intended for use by children. Ensure that it is stored in a safe place away from minors.
- **EU Contact Point:** For any safety inquiries, please refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Be aware of any safety alerts regarding this product through the EU Safety Gate system.

Specific Safety Precautions for Use

- **Use an Alignment Rod:** Always use an alignment rod to ensure that the muzzle brake is correctly positioned.
- **Clean Surfaces:** Before installation, make sure all surfaces are clean to prevent any issues with alignment or sealing.
- **Torque Specifications:**
 - Torque the muzzle device to approximately 30 ft lbs.
 - Torque the suppressor to 10 ft lbs.
- **Check Alignment:** Ensure that the muzzle device is square against the shoulder before attaching the silencer.
- **Avoid Warranty Voids:** Using the muzzle brake with a Q can may void your warranty. Use caution and follow the guidelines.
- **Proper Installation:** Follow the installation instructions carefully to prevent any accidents or malfunctions.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including an alignment rod, torque wrench, and cleaning materials.
- Ensure that the firearm is unloaded and in a safe condition before starting any installation.

2. Cleaning:

- Clean the muzzle of the barrel and the threads of the muzzle device thoroughly.

3. Alignment:

- Insert the alignment rod through the muzzle device to check for correct positioning.

4. Installation:

- Place the muzzle brake onto the barrel.
- Ensure that the muzzle device is square against the shoulder.

5. Torquing:

- Use a torque wrench to tighten the muzzle device to approximately 30 ft lbs.
- Apply Rocksett to secure the muzzle device to the barrel.
- Torque the suppressor to 10 ft lbs.

6. Final Check:

- After installation, doublecheck the alignment and torque settings.
- Make sure all components are secure before using the firearm.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the muzzle brake is no longer in use, follow local guidelines for the disposal of firearm accessories.
- Do not discard in regular household waste if the product is damaged or nonfunctional.

Contact Information for Further Support

For additional support or inquiries regarding the RPB Muzzle Brake, please refer to the contact information provided by your retailer or manufacturer. Always ensure that you are using the product in compliance with all safety regulations and guidelines.

Thank you for your attention to these safety instructions. Your safety and the safe operation of your firearm is our top priority. Enjoy using your RPB Muzzle Brake responsibly.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk