

R2 FLASH HIDER - REARDEN MANUFACTURING GROUP LLC R2 FLASH HIDER 1/2-28 THREADS SQUARE SHOULDER BLACK NITRIDE

[Rifle Parts](#) > [Muzzle Devices](#) > [Flash Hiders](#)

R2 FLASH HIDERS These fit Plan B type mounts. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 30 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH Atlas and Atlas XL compatible Plan B compatible Black Nitride finish (67 HRC Surface hardness) Shims not included, if you would like to specifically time this, shims will be required. Note: your barrel may require a shim if the manufacturer did not put a thread relief on it.



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC R2 FLASH HIDER 1/2-28 THREADS SQUARE SHOULDER BLACK NITRIDE](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111389
- Mfr. No.: 10083
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: 1/2-28
- Delivery weight: 0.227kg
- UPC: 850035804827

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [R2 Flash Hider Safety Instruction Guide](#)
- [About Us](#)

R2 Flash Hider Safety Instruction Guide

Introduction

Thank you for choosing the R2 Flash Hider from Rearden Manufacturing Group LLC. This product is designed to enhance your shooting experience while ensuring safety and reliability. Please read this safety instruction guide carefully to understand how to use and maintain the product safely.

General Safety Guidelines

- Ensure that the R2 Flash Hider is installed correctly to avoid any accidents.
- Always use an alignment rod when setting up the system to ensure proper alignment.
- Clean all surfaces thoroughly before installation to ensure a secure fit.
- Use Rockset to secure the muzzle device to the barrel.
- Avoid using the flash hider on a Q can, as this may void your warranty.
- Always torque the muzzle device to approximately 30 ftlbs.
- Ensure the muzzle device is square against the shoulder before installation.
- When attaching the suppressor, ensure that the threads and tapers are clean.
- Torque the suppressor to 10 ftlbs and ensure proper alignment.
- The nitride finish provides a tighter seal; therefore, proper installation is crucial.
- Regularly check the installation to ensure it remains secure.

Specific Safety Precautions for Use

- This product is designed for use with firearms that have a 1/228 thread pattern.
- Ensure you are of legal age to purchase and use this product in your jurisdiction.
- Keep the product out of reach of children and unauthorized users.
- Always wear appropriate eye and ear protection when using firearms equipped with this flash hider.
- Do not modify or alter the flash hider in any way, as this may compromise safety and performance.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including an alignment rod, torque wrench, and Rockset.
- Ensure the firearm is unloaded and safe to work on.

2. Cleaning

- Clean the barrel and muzzle device thoroughly to remove any debris or oil.
- Ensure that the threads are clean and free from any obstructions.

3. Installation

- Align the R2 Flash Hider with the barrel using the alignment rod.
- Once aligned, screw the flash hider onto the barrel by hand until snug.
- Use a torque wrench to tighten the muzzle device to approximately 30 ftlbs.
- Ensure the muzzle device is square against the shoulder.

4. Attaching the Suppressor

- Clean the threads and tapers of the suppressor thoroughly.
- Attach the suppressor to the flash hider.
- Torque the suppressor to 10 ftlbs, ensuring it is aligned properly.

5. Final Check

- Inspect the installation to ensure everything is secure and aligned.
- Perform a function check of the firearm to ensure proper operation.

Disposal Instructions

- Dispose of the R2 Flash Hider in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Contact your local waste management authority for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or support regarding the R2 Flash Hider, please refer to the official Rearden Manufacturing Group LLC website or contact your local dealer.

Please remember to report any unsafe products or accidents to the appropriate authorities and check for recall updates on the EU's Safety Gate platform. Your safety is our priority, and we encourage you to use this product responsibly. Enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk