

R2S FLASH HIDER - REARDEN MANUFACTURING GROUP LLC R2S FLASH HIDER 1/2-36 THREADS SQUARE SHOULDER BLACK

[Rifle Parts](#) > [Muzzle Devices](#) > [Flash Hiders](#)

R2S FLASH HIDERS These fit Plan B type mounts. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 15-25 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH Atlas and Atlas XL compatible Plan B compatible Black Nitride finish (67 HRC Surface hardness) Shims not included, if you would like to specifically time this, shims will be required. Note: your barrel may require a shim if the manufacturer did not put a thread relief on it.



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC R2S FLASH HIDER 1/2-36 THREADS SQUARE SHOULDER BLACK](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111403
- Mfr. No.: 10189
- Caliber: 40 Caliber
- Finish: Black
- Material: Stainless Steel
- Threads: 1/2-36
- Delivery weight: 0.227kg
- UPC: 850041491882

Item details

Made in USA

Table of Contents

- Startpage
- R2S FLASH HIDER SAFETY INSTRUCTION GUIDE
- About Us

R2S FLASH HIDER SAFETY INSTRUCTION GUIDE

Introduction

Thank you for choosing the R2S Flash Hider from Rearden Manufacturing Group LLC. This guide provides essential safety instructions and guidelines to ensure the safe use and installation of your product. Please read this document carefully to understand the safety precautions necessary for your protection and the proper functioning of the flash hider.

General Safety Guidelines

- Ensure that the R2S Flash Hider is used only with compatible firearms and accessories.
- Always follow the manufacturer's instructions and guidelines for installation and use.
- Regularly inspect the flash hider for signs of wear or damage. If any issues are found, discontinue use immediately.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about recall updates through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always use an alignment rod during installation to ensure correct setup.
- Clean all surfaces thoroughly before installation to prevent misalignment and ensure a proper seal.
- Torque the muzzle device to approximately 1525 ft lbs to secure it properly to the barrel.
- Ensure the muzzle device is square against the shoulder before attaching the silencer.
- When attaching the suppressor, clean the threads and tapers to avoid damage and ensure a tight fit.
- Torque the suppressor to 10 ft lbs to secure it effectively.
- Do not use the flash hider on a Q can, as this may void your warranty.
- If your barrel did not come with a thread relief, a shim may be required for proper installation.
- Use shims if you wish to time the installation specifically, as they are not included with the product.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools and materials, including an alignment rod, torque wrench, and cleaning supplies.
- Ensure that you are in a safe environment, free from distractions.

2. Cleaning

- Clean the barrel and muzzle device using appropriate cleaning materials to remove any dirt, oil, or debris.

3. Installation

- Align the R2S Flash Hider with the barrel using the alignment rod.
- Secure the muzzle device to the barrel by torquing it to 1525 ft lbs.
- Confirm that the muzzle device is square against the shoulder.
- Clean the threads and tapers of the suppressor before installation.
- Attach the suppressor to the muzzle device and torque it to 10 ft lbs.
- Doublecheck for alignment and ensure everything is secure.

4. PostInstallation

- After installation, inspect the assembly to ensure that all components are secure and properly aligned.
- Test the setup in a safe environment to confirm that it operates as expected.

Disposal Instructions

- Dispose of the R2S Flash Hider and any associated materials in accordance with local regulations.
- Do not dispose of the product in regular household waste. Check for designated disposal facilities for firearms accessories.

Contact Information for Further Support

For any inquiries regarding safety, installation, or product performance, please refer to the contact information provided by the retailer or manufacturer. It is essential to reach out for assistance if you have any doubts or concerns regarding the use of the R2S Flash Hider.

By following these guidelines, you can ensure the safe and effective use of your R2S Flash Hider. Thank you for your attention to safety and for choosing Rearden Manufacturing Group LLC.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk