

# R2S FLASH HIDER - REARDEN MANUFACTURING GROUP LLC R2S FLASH HIDER 13X1 LH THREADS FACEMOUNT SHOULDER BLACK

[Rifle Parts](#) > [Muzzle Devices](#) > [Flash Hiders](#)

R2S FLASH HIDERS These fit Plan B type mounts. Always use an alignment rod to ensure that the entire system is set up correctly. Make sure all surfaces are cleaned and the muzzle device has been torqued and Rockset to the barrel. Use on a Q can voids your warranty, be warned. Torque the muzzle device to approximately 15-25 ft lbs. Make sure the muzzle device is square against the shoulder. When setting the silencer on the muzzle device, ensure that the threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. FEATURES: 17-4 PH Atlas and Atlas XL compatible Plan B compatible Black Nitride finish (67 HRC Surface hardness) Shims not included, if you would like to specifically time this, shims will be required. Note: your barrel may require a shim if the manufacturer did not put a thread relief on it.



## Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC R2S FLASH HIDER 13X1 LH THREADS FACEMOUNT SHOULDER BLACK](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111404
- Mfr. No.: 10191
- Caliber: 40 Caliber
- Finish: Black
- Material: Stainless Steel
- Threads: M13x1LH
- Delivery weight: 0.227kg
- UPC: 850041491905

## Item details

Made in USA

# Table of Contents

- Startpage
- R2S FLASH HIDER SAFETY INSTRUCTION GUIDE
- About Us

# R2S FLASH HIDER SAFETY INSTRUCTION GUIDE

## Introduction

Thank you for choosing the R2S Flash Hider from Rearden Manufacturing Group LLC. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read all sections carefully before installation and use.

## General Safety Guidelines

- **Product Safety:** Ensure safe use of the R2S Flash Hider by following all instructions. This product is designed for use with firearms and should only be used by individuals knowledgeable about firearm safety.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices related to this product. If you receive a recall notice, follow the instructions provided.
- **Online Shopping:** If purchased online, ensure that the retailer complies with safety requirements. Verify the product upon arrival.
- **Special Consumer Focus:** This product is not intended for use by children. Always keep firearms and accessories out of reach of minors.
- **EU Contact Point:** For safety inquiries, please refer to your retailer or manufacturer for guidance.
- **Rapid Alerts:** Regularly check the EU's Safety Gate platform for updates on product safety.

## Specific Safety Precautions for Use

- **Read Instructions:** Before using the R2S Flash Hider, read this safety guide thoroughly.
- **Use Appropriate Tools:** Always use the correct tools for installation and maintenance to avoid damage or injury.
- **Inspect Before Use:** Check the flash hider for any signs of damage or wear before installation.
- **Proper Alignment:** Always use an alignment rod to ensure correct setup.
- **Cleaning:** Ensure all surfaces are clean before installation. This includes the muzzle device and the threads of the flash hider.
- **Torque Specifications:**
  - Torque the muzzle device to approximately 1525 ft lbs.
  - Torque the suppressor to 10 ft lbs.
- **Avoid Warranty voids:** Using the flash hider on a Q can void your warranty. Ensure compliance with all usage guidelines.
- **Nitride Finish Caution:** The nitride finish improves sealing but requires proper torque and Rockset application to the barrel to avoid issues.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools, including an alignment rod and a torque wrench.
- Ensure the firearm is unloaded and in a safe condition.

### 2. Installation:

- Clean the muzzle device and ensure threads are free of debris.
- Align the R2S Flash Hider with the muzzle device using the alignment rod.
- Securely attach the flash hider, ensuring it is square against the shoulder.
- Torque the muzzle device to the specified 1525 ft lbs.
- If using shims for timing, ensure they are properly placed. Note that shims are not included with the product.

### **3. Final Checks:**

- After installation, doublecheck all connections to ensure they are secure.
- Inspect alignment and ensure the suppressor is properly torqued to 10 ft lbs.

### **4. Usage:**

- Always follow firearm safety rules when using the flash hider with your firearm.
- Monitor for any unusual performance or signs of wear during use.

## **Disposal Instructions**

When disposing of the R2S Flash Hider, please follow local regulations regarding the disposal of firearm accessories. Ensure that all components are disposed of in an environmentally friendly manner. If you are unsure of the disposal process, consult local waste management authorities for guidance.

## **Contact Information for Further Support**

For any questions or concerns regarding the R2S Flash Hider, please refer to your retailer or the manufacturer. They can provide additional support and information as needed.

Thank you for your attention to these safety instructions. Proper care and adherence to these guidelines will help ensure a safe and enjoyable experience with your R2S Flash Hider.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)