

BLYAT MUZZLE BRAKES - REARDEN MANUFACTURING GROUP LLC

BLYAT XL MUZZLE BRAKE 24X1.5 THREAD FACEMOUNT SHOULDER BLACK

[Rifle Parts](#) > [Muzzle Devices](#) > [Compensators & Muzzle Brakes](#)

BLYAT MUZZLE BRAKES The Blyat attaches to our Atlas adapters, making them compatible with most suppressors on the market. These have 1 1/16" wrench flats on the rear; you can use a crows foot wrench, or our Atlas Wrench. The Blyat muzzle devices are designed to face mount on 24 and 26mm threads, helping to solve many common AK alignment issues.

FEATURES: Black Nitride Finish Atlas and Atlas XL Compatible Plan B Compatible Shims Included Always use an alignment rod to ensure that the entire system is set up correctly. To install your muzzle device, first make sure all surfaces are clean. Dry fit your muzzle device on your barrel with and without shims, and ensure proper alignment. Once you have the muzzle device aligned, you can rockset and torque it onto your barrel, again checking alignment. Torque the muzzle device to approximately 30 ft lbs. When attaching your silencer to your muzzle device, ensure that all threads and tapers are clean. Torque the suppressor to 10 ft lbs. Ensure alignment again. Enjoy. The nitride finish does lead to a tighter seal, with that said, it is extremely important to torque and rockset your muzzle device to the barrel properly. If you are unsure of how to properly install and align your muzzle device or suppressor, take it to a qualified gunsmith.



Attributes

- Name: [REARDEN MANUFACTURING GROUP LLC BLYAT XL MUZZLE BRAKE 24X1.5 THREAD FACEMOUNT SHOULDER BLACK](#)
- Manufacturer: [REARDEN MANUFACTURING GROUP LLC](#)
- Product no.: 430111414
- Mfr. No.: 10153
- Caliber: 375 Caliber (.375)
- Finish: Black
- Material: Stainless Steel
- Threads: M24x1.5
- Delivery weight: 0.227kg
- UPC: 850041491523

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for BLYAT XL Muzzle Brake
- About Us

Safety Instruction Guide for BLYAT XL Muzzle Brake

Introduction

Thank you for choosing the BLYAT XL Muzzle Brake from Rearden Manufacturing Group LLC. This guide provides essential safety information and instructions to ensure the safe use and installation of your muzzle brake. Please read this guide carefully before using the product.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the BLYAT XL Muzzle Brake by following all instructions. This product is intended for use with firearms and should be handled with care.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices related to this product. Regularly check for updates.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety requirements similar to physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For safety inquiries, please refer to the manufacturer's contact information provided with your product.
- **Rapid Alerts:** Stay updated on product safety through the EU's Safety Gate system.

Specific Safety Precautions for Use

- Always ensure that the muzzle brake is compatible with your firearm before installation.
- Use appropriate tools, such as a crows foot wrench or the Atlas Wrench, to avoid damaging the muzzle brake.
- Ensure that all threads and surfaces are clean before installation to prevent misalignment and ensure a secure fit.
- Always use an alignment rod when installing the muzzle device to ensure proper alignment.
- Do not exceed the recommended torque specifications when installing the muzzle brake or attaching a suppressor.
- Seek assistance from a qualified gunsmith if you are unsure about the installation or alignment process.

Instructions for Installation and Usage

1. Preparation:

- Ensure all surfaces of the muzzle brake and the firearm are clean.
- Dry fit the muzzle device on the barrel with and without shims to check alignment.

2. Installation:

- Align the muzzle brake with the barrel threads.
- If using shims, place them as needed to achieve proper alignment.
- Once aligned, use rockset to secure the muzzle brake onto the barrel.
- Torque the muzzle brake to approximately 30 ft lbs.

3. Attaching a Suppressor:

- Ensure all threads and tapers on the muzzle brake and suppressor are clean.
- Attach the suppressor and torque it to 10 ft lbs, ensuring proper alignment.

4. PostInstallation Check:

- After installation, check for proper alignment and secure fit.
- Test the firearm in a safe environment to ensure everything is functioning as intended.

Disposal Instructions

- Dispose of the product in accordance with local regulations. Do not dispose of in regular household waste.
- If the product is damaged or no longer in use, contact your local waste management authority for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the BLYAT XL Muzzle Brake, please refer to the manufacturer's contact information included with your product.

Thank you for your attention to these safety guidelines. Enjoy using your BLYAT XL Muzzle Brake responsibly and safely.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk