

# **BROWNING HI-POWER REAR SIGHTS - NOVAK TRIT. LM BRWN HP 2-DOT,FRT ST .190"-.205",RR BLD .700"X.275"**

[Handgun Parts](#) > [Sights](#) > [Rear Sights](#)

Competition plain, target-style, undercut blade with protected notch. Hangs over the rear of the slide and extends sight radius for quicker, more precise sighting. Browning HP require milling of slide, use 65° x .495" dovetail cutter. HP fits later models with external, side extractors only. Lo-Mount has an angled top surface with mitered edges that won't snag on holsters or clothes. Rebated blade fights glare. Browning Hi Power models fit the Mark II models.



## **Attributes**

- Name: [NOVAK TRIT. LM BRWN HP 2-DOT,FRT ST .190"-.205",RR BLD .700"X.275"](#)
- Manufacturer: [NOVAK](#)
- Product no.: 662002007
- Mfr. No.:
- Model: High Power
- Sight Color: Tritium
- Style: 2-Dot
- Weapon type: Browning
- Delivery weight: 0.018kg
- Shipping width: 57mm
- Shipping length: 89mm

## **Item details**

Made in USA

# Table of Contents

- Startpage
- Browning HiPower Rear Sights Safety Instruction Guide
- About Us

# Browning HiPower Rear Sights Safety Instruction Guide

## Introduction

Thank you for choosing the Browning HiPower Rear Sights. This guide provides important safety instructions and information to ensure the safe use and installation of your product. Please read this guide carefully before use.

## General Safety Guidelines

- Ensure that the Browning HiPower Rear Sights are installed by a qualified gunsmith to avoid any risks associated with improper installation.
- Always handle your firearm with care, following all safety protocols.
- Regularly inspect your sights and firearm for any signs of wear or damage.
- Keep the product out of reach of children and unauthorized users.
- Do not use the product if it appears damaged or malfunctioning.
- Report any unsafe products or accidents to the relevant authorities immediately.
- Check for recall updates on the EU's Safety Gate platform to stay informed about safety issues.

## Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before installing or adjusting the sights.
- Use the correct tools as specified for installation, including a  $65^\circ \times .495"$  dovetail cutter for milling the slide.
- Only use the Browning HiPower Rear Sights on compatible models, specifically those with external, side extractors.
- Avoid using the firearm in lowlight conditions without adequate external light sources, as this may affect sight visibility.
- Be cautious when holstering or drawing your firearm to prevent snagging on clothing or holsters due to the LoMount design.
- Be aware that the rebated blade is designed to reduce glare; however, it is still important to ensure proper lighting conditions for optimal sighting.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure your firearm is completely unloaded.
- Gather necessary tools, including the specified dovetail cutter.

### 2. Milling the Slide

- Using the  $65^\circ \times .495"$  dovetail cutter, carefully mill the slide of your Browning HiPower to accommodate the new sights.
- Ensure that the milling is done by a qualified gunsmith to prevent any damage.

### 3. Installing the Sights

- Align the Browning HiPower Rear Sights with the milled dovetail.
- Secure the sights in place according to the manufacturer's specifications.
- Check that the sights are firmly attached and do not move when pressure is applied.

### 4. Sight Adjustment

- Once installed, adjust the sights as needed for optimal accuracy.
- Test the alignment by aiming at a target and making necessary adjustments.

## 5. Maintenance

- Regularly clean the sights and inspect for any signs of wear.
- Ensure that the sight picture remains clear and unobstructed.

## Disposal Instructions

- Dispose of any packaging materials in accordance with local waste management regulations.
- If the product is no longer in use, consider recycling or disposing of it in a manner that complies with local environmental laws.
- Do not dispose of the product in regular household waste if it contains hazardous materials.

## Contact Information for Further Support

For any questions or further support regarding your Browning HiPower Rear Sights, please refer to the manufacturer's contact information found on the product packaging or official website. Ensure you have the product details ready for quicker assistance.

By following these guidelines, you can ensure the safe and effective use of your Browning HiPower Rear Sights. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)