

SINCLAIR STAINLESS STEEL PILOTS - SINCLAIR INTERNATIONAL PILOT STOP, STAINLESS STEEL, 45 CALIBER

[Reloading](#) > [Case Preparation](#) > [Flash Hole Tool Pilots](#)

We manufacture pilots for our flash hole tool and our Neck Thickness/Variance Gauge. Our pilots are precision machined from stainless steel on CNC turning centers to properly fit new, unfired case necks. Available for rifle and pistol cartridges from 22 thru 45 caliber. Not for use on .50 BMG. 50 BMG flash hole diameter is larger.



Attributes

- Name: [SINCLAIR INTERNATIONAL PILOT STOP, STAINLESS STEEL, 45 CALIBER](#)
- Manufacturer: [SINCLAIR INTERNATIONAL](#)
- Product no.: 749001000
- Mfr. No.: 26458
- Caliber: 45 Caliber (.451-.454)
- Delivery weight: 0.015kg
- Shipping height: 6mm
- Shipping width: 83mm
- Shipping length: 140mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Sinclair Stainless Steel Pilots](#)
- [About Us](#)

Safety Instruction Guide for Sinclair Stainless Steel Pilots

Introduction

Thank you for choosing the Sinclair Stainless Steel Pilots manufactured by Sinclair International. This guide provides essential safety instructions and information to ensure the safe and effective use of our product. Please read this document carefully before using the pilots.

General Safety Guidelines

- Always ensure that the pilots are compatible with the specific caliber of your flash hole tool and Neck Thickness/Variance Gauge.
- Inspect the pilots for any signs of damage or wear before each use. Do not use damaged pilots.
- Keep the pilots out of reach of children and vulnerable individuals.
- Follow all local laws and regulations regarding the use of firearms and ammunition.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Use only with unfired case necks to avoid misalignment and potential accidents.
- Do not attempt to use the pilots with .50 BMG ammunition, as the flash hole diameter is larger and may cause malfunction.
- Wear appropriate safety gear, including eye protection, when using the flash hole tool and pilots.
- Ensure that your workspace is clean and free from distractions to maintain focus during use.
- Do not exceed the recommended specifications for the pilots, including caliber limits.

Instructions for Installation and Usage

1. Preparation:

- Ensure that you have the correct pilot for your caliber (45 Caliber: .451.454).
- Gather all necessary tools and equipment before starting.

2. Installation:

- Insert the pilot into the designated slot of the flash hole tool or Neck Thickness/Variance Gauge.
- Ensure that the pilot is securely seated and properly aligned.

3. Usage:

- Carefully follow the operating instructions for your flash hole tool or Neck Thickness/Variance Gauge.
- Apply gentle and even pressure when using the tool to avoid damaging the pilot or the case neck.
- Regularly check the alignment and condition of the pilot during use.

4. PostUsage:

- Clean the pilots after each use to remove any debris or residue.
- Store the pilots in a safe, dry place away from direct sunlight and moisture.

Disposal Instructions

- Dispose of any damaged or worn pilots in accordance with local waste disposal regulations.
- Do not dispose of pilots in regular household waste if they are considered hazardous materials.
- Check with local authorities for proper disposal methods for stainless steel products.

Contact Information for Further Support

For any inquiries regarding safety, usage, or product information, please contact the manufacturer directly. Ensure you have the product details ready for a prompt response.

By following these safety instructions, you can ensure a safe and effective experience with your Sinclair Stainless Steel Pilots. Please keep this guide for future reference.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk