

# MAXIMA QUICK DETACH RINGS - 1" DIAMETER ULTRA HIGH (.935") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

## Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



## Attributes

- Name: [1" DIAMETER ULTRA HIGH \(.935"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000005
- Mfr. No.: 204LM
- Finish: Matte Blue
- Height: .935"
- Scope Tube Diameter: 1"
- Size: Ultra High
- Style: Weaver-Style Rings
- Delivery weight: 0.249kg
- Shipping height: 23mm
- Shipping width: 112mm
- Shipping length: 155mm
- UPC: 656813000753

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for MAXIMA QUICK DETACH RINGS 1" DIAMETER ULTRA HIGH (.935") QD RINGS BLACK
- About Us

# Safety Instruction Guide for MAXIMA QUICK DETACH RINGS 1" DIAMETER ULTRA HIGH (.935") QD RINGS BLACK

## Introduction

Thank you for choosing the MAXIMA Quick Detach Rings. This guide provides important safety information and instructions to ensure the safe and effective use of the product. Please read this guide carefully before installation and use.

## General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a mounting system for optics.
- Always inspect the rings and mounts for any signs of damage before use.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Follow all installation and usage instructions provided in this guide to avoid potential hazards.
- Report any unsafe products or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- **Installation Precautions:**
  - Ensure that the mounting surface is clean and free from debris before installation.
  - Use the appropriate tools as specified for tightening screws to prevent overtightening, which may damage the rings or the scope.
- **Usage Precautions:**
  - Always check that the rings are securely fastened before using the firearm.
  - Avoid using the rings in extreme temperatures or environmental conditions that may affect their performance.
  - Regularly check the positioning of the rings and the scope to ensure they have not shifted during use.
- **Recoil Control:**
  - Be aware that the recoil control key is designed to prevent movement under recoil. Ensure it is properly engaged during installation.

## Instructions for Installation and Usage

### 1. Installation:

- Gather the necessary tools: Torx style T15 screwdriver.
- Clean the mounting area on the rifle to ensure a secure fit.
- Position the Maxima QD rings on the Warne bases or compatible Weaver cross slot and MilSpec Picatinny style bases.
- Insert the Torx screws into the rings and tighten them securely, ensuring not to overtighten.
- Adjust the lever position by pulling it out, turning it to the desired location, and letting it snap into place.

### 2. Usage:

- Before using the firearm, doublecheck that the scope is properly mounted and secure.
- When detaching the scope, ensure the lever is fully engaged before removing or reattaching the optics.
- After reattaching, verify that the zero has been maintained by performing a test shot.

## **Disposal Instructions**

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- When disposing of the product itself, ensure it is done in an environmentally responsible manner, adhering to local electronic waste disposal guidelines.

## **Contact Information for Further Support**

For any questions or concerns regarding the MAXIMA Quick Detach Rings, please refer to the manufacturer's contact information provided on the packaging or product documentation.

Thank you for your attention to these safety instructions. Your safety is our priority, and we hope you enjoy using the MAXIMA Quick Detach Rings.

# About Us

## **Brownells Česká republika**

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.cz](http://www.brownells.cz)