

# MAXIMA QUICK DETACH RINGS - 30MM ULTRA HIGH (0.85") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

## Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



## Attributes

- Name: [30MM ULTRA HIGH \(0.85"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000010
- Mfr. No.: 217LM
- Finish: Matte Blue
- Height: .850"
- Scope Tube Diameter: 30mm
- Size: Ultra High
- Style: Weaver-Style Rings
- Delivery weight: 0.249kg
- Shipping height: 15mm
- Shipping width: 114mm
- Shipping length: 157mm
- UPC: 656813000852

## Item details

Made in USA

# Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS 30MM ULTRA HIGH (0.85") QD RINGS BLACK Safety Instruction Guide
- About Us

# MAXIMA QUICK DETACH RINGS 30MM ULTRA HIGH (0.85") QD RINGS BLACK Safety Instruction Guide

## Introduction

Thank you for purchasing the MAXIMA QUICK DETACH RINGS 30MM ULTRA HIGH (0.85") QD RINGS BLACK. These rings are designed to provide a secure and reliable mounting solution for your optics. This guide outlines essential safety instructions and guidelines to ensure the safe and effective use of this product.

## General Safety Guidelines

- Always read and understand the user manual before using the product.
- Ensure that the product is suitable for your specific firearm and optics.
- Regularly inspect the rings for signs of wear or damage.
- Store the product in a safe and dry environment when not in use.
- Follow all local laws and regulations regarding firearm accessories.

## Specific Safety Precautions for Use

- Recoil Management:** Ensure that the recoil control key is properly engaged to prevent movement of the rings during firing.
- Installation:** Only use the recommended tools (Torx style T15 socket cap screws) for installation to avoid stripping screws.
- Adjustment:** When adjusting the lever, do so gently to avoid damaging the mechanism.
- Child Safety:** Keep the product out of reach of children to prevent accidental injury.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools, including a Torx T15 screwdriver.
- Ensure that the firearm is unloaded and pointed in a safe direction.

### 2. Installation:

- Align the rings with the Warne bases or compatible Weaver cross slot and MilSpec Picatinny style bases.
- Insert the Torx screws into the rings and tighten them securely without overtorquing.
- Engage the recoil control key by ensuring it fits snugly into the recoil slot.

### 3. Optics Attachment:

- Place your optics into the rings.
- Tighten the levers until secure, ensuring the optics are held firmly in place.
- Adjust the lever position by pulling out and rotating it to the desired location before snapping it back into place.

### 4. Final Check:

- Verify that the optics are securely mounted and that there is no movement when the firearm is fired.
- Check the alignment and ensure that the zero is maintained after reattaching the optics.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for metal and electronic waste.
- Do not dispose of the product in general household waste.
- Consider recycling options where available to minimize environmental impact.

## Contact Information for Further Support

For any safety inquiries or concerns regarding the MAXIMA QUICK DETACH RINGS, please consult the manufacturer's website or customer service resources. Ensure you have the product details available when seeking assistance.

By following these safety instructions, you can ensure a safe and effective experience with your MAXIMA QUICK DETACH RINGS. Always prioritize safety and adhere to best practices when handling firearm accessories.

# About Us

## **Brownells Česká republika**

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.cz](http://www.brownells.cz)