

# MAXIMA QUICK DETACH RINGS - 34MM MEDIUM (.375") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

## Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



## Attributes

- Name: [34MM MEDIUM \(.375"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000257
- Mfr. No.: 221LM
- Finish: Matte Blue
- Height: .375"
- Scope Tube Diameter: 34mm
- Size: Medium
- Style: Weaver-Style Rings
- Delivery weight: 0.204kg
- Shipping height: 23mm
- Shipping width: 114mm
- Shipping length: 157mm
- UPC: 656813102419

## Item details

Made in USA

# Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS 34MM MEDIUM (.375") QD RINGS BLACK Safety Instruction Guide
- About Us

# MAXIMA QUICK DETACH RINGS 34MM MEDIUM (.375") QD RINGS BLACK Safety Instruction Guide

## Introduction

Thank you for choosing the MAXIMA QUICK DETACH RINGS 34MM MEDIUM (.375") QD RINGS BLACK. These rings are designed for the secure and reliable mounting of optical devices on your firearm. This safety instruction guide is provided to ensure the safe use of this product in compliance with the EU General Product Safety Regulation (GPSR).

## General Safety Guidelines

- Always ensure that your firearm is unloaded before installing or adjusting the scope rings.
- Regularly inspect the rings for any signs of wear or damage.
- Ensure that all components are properly tightened before use to prevent any accidents.
- Keep this product out of reach of children and unauthorized users.
- Always follow the manufacturer's instructions when using this product.

## Specific Safety Precautions for Use

- Use only with compatible Warne bases, Weaver cross slot, or MilSpec Picatinny style bases and rails.
- Ensure that the scope tube diameter matches the ring specifications (34mm) to avoid damage.
- Do not exceed the recommended torque specifications when tightening the screws to prevent stripping or damaging the rings.
- Avoid using this product in extreme environmental conditions that may affect performance, such as heavy rain or extreme temperatures.
- If you notice any unusual movement or looseness in the rings during use, stop using the product immediately and inspect it.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure your firearm is unloaded and in a safe condition.
- Gather all necessary tools, including a Torx T15 screwdriver.

### 2. Installation:

- Place the Maxima QD rings onto the Warne base or compatible rail.
- Align the rings so that they are parallel and at the desired height.
- Insert the Torx T15 socket cap screws into the ring's base and handtighten.

### 3. Securing the Rings:

- Use the Torx T15 screwdriver to tighten the screws to the manufacturer's recommended torque specifications.
- Ensure the unique Warne indexable lever system is correctly positioned for easy access.

### 4. Attaching the Scope:

- Carefully place your scope into the rings, ensuring it is correctly aligned.
- Tighten the rings around the scope, ensuring a secure fit without overtightening.

### 5. Final Check:

- After installation, check that the scope is properly secured and that there is no movement.
- Confirm that the levers are in the desired position and are functioning correctly.

## **Disposal Instructions**

- Dispose of the product in accordance with local regulations regarding steel and electronic waste.
- Do not dispose of this product in general household waste.
- Consider recycling components where possible to minimize environmental impact.

## **Contact Information for Further Support**

For any safety inquiries or further assistance regarding the MAXIMA QUICK DETACH RINGS, please consult your local retailer or visit the manufacturer's website for additional resources and support.

By following the guidelines outlined in this safety instruction guide, you can ensure the safe and effective use of the MAXIMA QUICK DETACH RINGS 34MM MEDIUM (.375") QD RINGS BLACK. Thank you for your attention to safety and compliance.

# About Us

## **Brownells Česká republika**

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.cz](http://www.brownells.cz)