

MAXIMA QUICK DETACH RINGS - WARNE MFG. COMPANY 1" MEDIUM (0.375") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: [WARNE MFG. COMPANY 1" MEDIUM \(0.375"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947623100
- Mfr. No.: 201LM
- Finish: Matte Blue
- Height: .375"
- Scope Tube Diameter: 1"
- Size: Medium
- Style: Weaver-Style Rings
- Delivery weight: 0.159kg
- Shipping height: 23mm
- Shipping width: 109mm
- Shipping length: 145mm
- UPC: 656813000296

Item details

Made in USA

Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTION GUIDE
- About Us

MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTION GUIDE

Introduction

Thank you for choosing the Maxima Quick Detach Rings by Warne MFG. Company. This guide provides important safety information and instructions to ensure the safe and effective use of your scope rings. Please read this guide carefully before installation and use.

General Safety Guidelines

- **Product Safety:** Ensure safe handling and use of the Maxima Quick Detach Rings. Follow all guidelines to minimize risks associated with the product.
- **Enhanced Recalls:** Be aware of recall notices. If a recall occurs, follow the instructions provided for a free remedy.
- **Online Shopping:** When purchasing online, ensure that the seller complies with safety requirements similar to physical stores.
- **Special Consumer Focus:** Extra care should be taken when using this product around vulnerable groups, such as children.
- **EU Contact Point:** For safety inquiries, ensure you have access to an EUbased contact.
- **Rapid Alerts:** Stay informed about product safety updates via the EU Safety Gate platform.

Specific Safety Precautions for Use

- **Installation:** Ensure that the rings are installed correctly to avoid any accidents. Incorrect installation can lead to scope misalignment or detachment.
- **Recoil Control:** Always check that the recoil control key is properly engaged to prevent movement during use.
- **Weight Limit:** Ensure that the scope mounted on the rings does not exceed the weight limit recommended by the manufacturer.
- **Inspect Regularly:** Periodically inspect the rings and mounting system for signs of wear or damage.
- **Avoid Modifications:** Do not modify the rings or mounting system, as this can compromise safety and performance.
- **Environmental Considerations:** Avoid exposing the rings to extreme temperatures or corrosive environments that could affect their integrity.

Instructions for Installation and Usage

1. Preparation:

- Ensure you have all necessary tools, including a Torx T15 screwdriver.
- Gather your scope and Warne bases.

2. Installation:

- Align the Maxima Quick Detach Rings with the Warne bases.
- Secure each ring using the Torx T15 socket cap screws. Tighten screws evenly to ensure a secure fit.
- Once installed, check that the rings are firmly attached to the bases.

3. Mounting the Scope:

- Carefully place the scope into the rings.

- Adjust the position of the scope as needed for optimal eye relief and alignment.
- Tighten the rings gradually, alternating between them to maintain even pressure.

4. Using the Quick Detach Feature:

- To detach the scope, pull out on the lever and turn it to the desired position.
- Release the lever to snap it back into place securely.
- To reattach, follow the same steps and ensure the scope is aligned correctly.

5. PostUse Inspection:

- After use, check that the rings have maintained their position and that there is no movement.
- Clean the rings with a soft cloth to remove dirt or debris.

Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling guidelines.
- When disposing of the Maxima Quick Detach Rings, consider recycling the metal components where facilities are available.
- Do not dispose of the product in household waste.

Contact Information for Further Support

For additional support, please refer to the manufacturer's website or consult your retailer for assistance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk