

# USL-Mounts - USL-Mont. for Shield, Optical Axis Height 27,8mm

Ultra-slim profile: Prevents snagging on top-mounted charging handles.

Streamlined design: No protruding parts to get caught on gear.



Lightweight construction: Optimized design for minimal weight impact.

100% recoil-proof: Guarantees absolute repeatability under heavy recoil.

Secure lever lock: Features a reliable locking mechanism with an integrated pawl.

Adjustable tension: Clamping force on the Picatinny rail can be finely adjusted.

Premium materials: CNC-machined from solid, high-strength 7075 aluminum.

Heavy-duty components: All functional parts are made of tempered stainless steel.

Mil-Spec finish: Matte black hard-anodized according to MIL-SPEC Type III.

## Attributes

- Name: USL-Mont. for Shield, Optical Axis Height 27,8mm
- Manufacturer: ERATAC
- Product no.: EU2018100
- Mfr. No.: T6122-0028
- Colour: Black
- Delivery weight: 0.0623kg
- Shipping height: 55mm
- Shipping width: 80mm
- Shipping length: 95mm
- EAN/UPC: T6122-0028

# Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for USLMounts USLMont for Shield](#)

# Safety Instruction Guide for USLMounts USLMont for Shield

## Introduction

Thank you for choosing the USLMounts USLMont for Shield. This guide provides essential safety information and instructions to ensure the safe use and installation of this product. Please read this guide carefully before use to maximize safety and performance.

## General Safety Guidelines

- Always ensure the product is used in accordance with the manufacturer's instructions.
- Inspect the product for any damage before installation and use.
- Do not use the product if any parts are damaged or missing.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the relevant authorities.
- Stay informed about product recalls or safety updates via the EU Safety Gate platform.

## Specific Safety Precautions for Use

- Ensure that the mounting surface is clean and free of debris before installation.
- Avoid using excessive force when tightening the clamping mechanism to prevent damage.
- Regularly check the clamping force to ensure it remains secure during use.
- Do not exceed the recommended weight limits for mounted accessories.
- Be cautious when handling the product, as sharp edges may exist.
- Use only compatible accessories that are designed for use with this mount.

## Instructions for Installation and Usage

### 1. Installation Steps:

- Ensure that you have all components of the USLMounts USLMont for Shield.
- Clean the Picatinny rail on your firearm to ensure proper adhesion.
- Position the mount on the Picatinny rail at the desired location.
- Adjust the clamping mechanism to fit securely on the rail.
- Use the secure lever lock to fasten the mount in place.
- Finetune the adjustable tension to achieve the desired clamping force.

### 2. Usage Instructions:

- Always ensure the mount is securely fastened before use.
- Regularly check the mount during use, especially after heavy firing sessions.
- If you notice any movement or looseness, stop using the product immediately and recheck the installation.
- Follow all standard firearm safety practices when using your firearm with the mount.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- Consider recycling the product if possible, as it is made from highstrength aluminum and stainless steel.

## **Contact Information for Further Support**

For any inquiries regarding safety, usage, or product support, please contact the manufacturer directly through their official channels. Ensure you have your product details ready for efficient assistance.

By following these guidelines, you can ensure a safe and effective experience with your USLMounts USLMont for Shield. Thank you for prioritizing safety and compliance.