

USL-Mounts - USL-Mont. for Shield, Optical Axis Height 39,0mm

Ultra-slim profile: Prevents snagging on top-mounted charging handles.

Streamlined design: No protruding parts to get caught on gear.



Lightweight construction: Optimized design for minimal weight impact.

100% recoil-proof: Guarantees absolute repeatability under heavy recoil.

Secure lever lock: Features a reliable locking mechanism with an integrated pawl.

Adjustable tension: Clamping force on the Picatinny rail can be finely adjusted.

Premium materials: CNC-machined from solid, high-strength 7075 aluminum.

Heavy-duty components: All functional parts are made of tempered stainless steel.

Mil-Spec finish: Matte black hard-anodized according to MIL-SPEC Type III.

Attributes

- Name: USL-Mont. for Shield, Optical Axis Height 39,0mm
- Manufacturer: ERATAC
- Product no.: EU2018101
- Mfr. No.: T6122-0039
- Colour: Black
- Delivery weight: 0.0711kg
- Shipping height: 55mm
- Shipping width: 80mm
- Shipping length: 95mm
- EAN/UPC: T6122-0039

Table of Contents

- [Startpage](#)
- [English: USLMounts USLMont Safety Instructions](#)

USLMounts USLMont Safety Instructions

Introduction

Thank you for choosing the USLMounts USLMont for Shield. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this document carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the product for any signs of wear or damage.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all local laws and regulations regarding the use of firearm accessories.
- Report any unsafe products or accidents to the relevant authorities.
- Stay updated on recall notices through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Product Integrity:** Do not modify the product in any way. Modifications may compromise safety and performance.
- **Installation:** Ensure the product is installed correctly according to the instructions below. Improper installation can lead to malfunctions.
- **Handling:** Always handle the product with care, especially when it is attached to a firearm. Avoid dropping or striking the product against hard surfaces.
- **Recoil Management:** The product is designed to be 100% recoilproof; however, ensure that your firearm is properly maintained to minimize recoil effects.
- **Clamping Force:** Adjust the clamping force on the Picatinny rail carefully. Too much force may damage the rail, while too little may result in instability.

Instructions for Installation and Usage

1. Installation:

- Clean the Picatinny rail area thoroughly to ensure a secure fit.
- Position the USLMont on the Picatinny rail at the desired location.
- Adjust the lever lock to secure the mount in place.
- Use the adjustable tension feature to finetune the clamping force as needed.

2. Usage:

- Always check that the mount is securely locked before use.
- Avoid using the product in extreme conditions that may affect its performance.
- Regularly check for any signs of wear or loosening of the mount during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations for metal and electronic waste.
- Do not dispose of the product in regular household waste.
- Check with your local waste management facility for proper disposal methods.

Contact Information for Further Support

For any inquiries or concerns regarding your USLMounts USLMont, please refer to the manufacturer's contact information provided in the product packaging.