

USL-Mounts - USL-Mount for Docter/NOBLEX, Optical Axis Height 39,0mm

Ultra-slim profile: Prevents snagging on top-mounted charging handles.

Streamlined design: No protruding parts to get caught on gear.



Lightweight construction: Optimized design for minimal weight impact.

100% recoil-proof: Guarantees absolute repeatability under heavy recoil.

Secure lever lock: Features a reliable locking mechanism with an integrated pawl.

Adjustable tension: Clamping force on the Picatinny rail can be finely adjusted.

Premium materials: CNC-machined from solid, high-strength 7075 aluminum.

Heavy-duty components: All functional parts are made of tempered stainless steel.

Mil-Spec finish: Matte black hard-anodized according to MIL-SPEC Type III.

Attributes

- Name: USL-Mount for Docter/NOBLEX, Optical Axis Height 39,0mm
- Manufacturer: ERATAC
- Product no.: EU2018105
- Mfr. No.: T6160-0039
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T6160-0039

Table of Contents

- [Startpage](#)
- [English: USLMount for Docter/NOBLEX Safety Instructions](#)

USLMount for Docter/NOBLEX Safety Instructions

Introduction

Thank you for choosing the USLMount for Docter/NOBLEX. This product is designed to enhance your shooting experience by providing a secure and reliable mounting solution. Please read this safety instruction guide carefully to ensure safe usage and compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure the product is used only for its intended purpose as a mounting solution for optics.
- Always inspect the USLMount before use to check for any signs of wear or damage.
- Keep the product out of reach of children and vulnerable individuals.
- In case of any malfunction or damage, cease use immediately and report it to the appropriate authorities.
- Stay informed about safety recalls and updates through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Recoil Management:** The USLMount is designed to be 100% recoilproof. However, ensure that it is securely locked in place before use to avoid any accidents.
- **Installation Safety:** Follow the installation instructions carefully to prevent improper mounting which could lead to equipment failure.
- **Weight Considerations:** The lightweight construction is optimized for minimal weight impact, but ensure that your firearm can handle the additional weight without compromising safety.
- **Environmental Conditions:** Avoid using the USLMount in extreme weather conditions that may affect its performance or integrity.

Instructions for Installation and Usage

1. Installation:

- Begin by ensuring that the Picatinny rail on your firearm is clean and free of debris.
- Align the USLMount with the rail, ensuring that the clamping mechanism is positioned correctly.
- Secure the mount by tightening the adjustable tension lever. Ensure that the clamping force is finely adjusted for a secure fit.

2. Usage:

- After installation, check that the mount is firmly attached and does not move when pressure is applied.
- Attach your optic to the USLMount according to the manufacturer's instructions for that specific device.
- Always check the tightness of the mount and optic before each use to ensure safety.

Disposal Instructions

- Dispose of the USLMount in accordance with local regulations regarding electronic and metal waste.
- Do not dispose of the product in regular household waste. Instead, take it to a designated recycling facility or follow local disposal guidelines.

Contact Information for Further Support

For any inquiries regarding safety, usage, or product support, please refer to the manufacturer's website or

contact your local distributor for assistance.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priority.