

USL-Mounts - USL-Mount for Trijicon RMR, Optical Axis Height 29,5mm

Ultra-slim profile: Prevents snagging on top-mounted charging handles.

Streamlined design: No protruding parts to get caught on gear.



Lightweight construction: Optimized design for minimal weight impact.

100% recoil-proof: Guarantees absolute repeatability under heavy recoil.

Secure lever lock: Features a reliable locking mechanism with an integrated pawl.

Adjustable tension: Clamping force on the Picatinny rail can be finely adjusted.

Premium materials: CNC-machined from solid, high-strength 7075 aluminum.

Heavy-duty components: All functional parts are made of tempered stainless steel.

Mil-Spec finish: Matte black hard-anodized according to MIL-SPEC Type III.

Attributes

- Name: USL-Mount for Trijicon RMR, Optical Axis Height 29,5mm
- Manufacturer: ERATAC
- Product no.: EU2018106
- Mfr. No.: T6180-0029
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T6180-0029

Table of Contents

- [Startpage](#)
- [English: USLMounts USLMount for Trijicon RMR Safety Instruction Guide](#)

USLMounts USLMount for Trijicon RMR Safety Instruction Guide

Introduction

Thank you for choosing the USLMounts USLMount for Trijicon RMR. This product is designed to enhance your shooting experience by providing a secure and reliable mounting solution. Please read this safety instruction guide carefully to ensure safe usage and installation of your product.

General Safety Guidelines

- Always ensure that the USLMount is installed correctly before use.
- Regularly inspect the mount for any signs of wear or damage.
- Do not exceed the manufacturer's recommended specifications for mounting.
- Keep the product away from children and vulnerable individuals.
- Always follow local laws and regulations regarding the use of firearm accessories.

Specific Safety Precautions for Use

- Ensure that the mount is compatible with your Trijicon RMR before installation.
- Do not modify the mount in any way, as this may compromise its safety and functionality.
- Use only the recommended tools for installation to prevent damage.
- Avoid using the mount in extreme environmental conditions (e.g., excessive heat, cold, or humidity).
- If you notice any unusual behavior during use, stop using the product immediately and seek assistance.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench and the mounting screws provided with the product.
- Ensure that the Trijicon RMR and the Picatinny rail are clean and free of debris.

2. Installation:

- Align the USLMount with the Picatinny rail on your firearm.
- Secure the mount using the provided screws, ensuring they are tightened to the manufacturer's recommended torque specifications.
- Adjust the clamping force if necessary to ensure a secure fit.

3. Usage:

- After installation, check the stability of the mount by gently shaking it to ensure it is secure.
- Always handle your firearm in a safe manner, following all standard firearm safety practices.
- Regularly check the mount for tightness and functionality during use, especially after heavy shooting sessions.

Disposal Instructions

- Dispose of the USLMount responsibly in accordance with local waste management regulations.
- If the mount is damaged or no longer usable, consider recycling the aluminum and stainless steel components where possible.

Contact Information for Further Support

For any safety inquiries or concerns, please refer to the product packaging for contact details or consult the retailer where you purchased the product.

Thank you for your attention to these safety guidelines. Enjoy your shooting experience with the USLMounts USLMount for Trijicon RMR.