

USL-Mounts - USL-Mount for Trijicon RMR, Optical Axis Height 39,0mm

Ultra-slim profile: Prevents snagging on top-mounted charging handles.

Streamlined design: No protruding parts to get caught on gear.



Lightweight construction: Optimized design for minimal weight impact.

100% recoil-proof: Guarantees absolute repeatability under heavy recoil.

Secure lever lock: Features a reliable locking mechanism with an integrated pawl.

Adjustable tension: Clamping force on the Picatinny rail can be finely adjusted.

Premium materials: CNC-machined from solid, high-strength 7075 aluminum.

Heavy-duty components: All functional parts are made of tempered stainless steel.

Mil-Spec finish: Matte black hard-anodized according to MIL-SPEC Type III.

Attributes

- Name: USL-Mount for Trijicon RMR, Optical Axis Height 39,0mm
- Manufacturer: ERATAC
- Product no.: EU2018107
- Mfr. No.: T6180-0039
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T6180-0039

Table of Contents

- [Startpage](#)
- [English: USLMount for Trijicon RMR Safety Instruction Guide](#)

USLMount for Trijicon RMR Safety Instruction Guide

Introduction

Thank you for choosing the USLMount for Trijicon RMR. This guide provides essential safety instructions and guidelines to ensure the safe use of this product. Please read this document carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the mount for any signs of wear or damage.
- Avoid using the mount in extreme weather conditions that may affect its performance.
- Do not modify or alter the product in any way, as this may compromise safety.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or incidents to the relevant authorities.

Specific Safety Precautions for Use

- Always ensure the mount is securely attached to the firearm before use.
- Check the tension of the clamping force regularly to ensure it is properly adjusted.
- Be aware of the recoil impact when using the firearm with the mount attached.
- Use only compatible accessories with the mount to avoid safety hazards.
- Follow the manufacturer's recommendations for maintenance and care.

Instructions for Installation and Usage

Installation Steps

1. **Prepare the Firearm:** Ensure that the firearm is unloaded and pointed in a safe direction.
2. **Align the Mount:** Position the USLMount onto the Picatinny rail of the firearm.
3. **Adjust Tension:** Use the integrated pawl to adjust the clamping force as needed for a secure fit.
4. **Secure the Lock:** Engage the secure lever lock to ensure the mount is firmly attached.
5. **Final Check:** Doublecheck that the mount is stable and does not wobble before use.

Usage Guidelines

- When aiming, ensure that the optical axis height is aligned with your eye level for optimal performance.
- Practice safe handling of the firearm at all times, following all relevant laws and regulations.
- After use, inspect the mount and firearm for any signs of damage or wear.

Disposal Instructions

- Dispose of the product in accordance with local waste disposal regulations.
- Recycle materials whenever possible to minimize environmental impact.
- Do not dispose of the product in regular household waste if it contains hazardous materials.

Contact Information for Further Support

For any questions or concerns regarding the USLMount for Trijicon RMR, please refer to the manufacturer's customer service or support resources. Ensure that you have the product information ready when seeking assistance.

Thank you for your attention to these safety instructions. Your adherence to these guidelines helps ensure a safe and effective experience with your USLMount for Trijicon RMR.